LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 95 FILED

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 11	T. 2 N. S., R. 2 E. W.	I-4,I-5,J-4,J-5,K-5
2. PROPERTY CONTROLLING IN SECTION ____	T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION ____	T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

'74 APR 16 AM 11

JULIA C. BLACKBURN
REGISTER OF DEEDS
LIVINGSTON COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram — over) were, in a field survey on November 30 19 73, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__ , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

FILED

A. Description of original monument and accessories and/or subsequent restoration:

I-4 unknown
I-5 Unknown
J-4 Unknown
J-5 Unknown
K-5 Unknown

APR 25 9 20 AM '74
REGISTER OF DEEDS
Enid M. Lewis
INGHAM COUNTY, MICH.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-4 1/2" bolt fd.
I-5 1/2" bolt fd.
J-4 set 1/2" iron, fence intersection
J-5 set 1/2" iron, split mile from SW corner, Sec. 11 to SE cor. Sec. 11
K-5 nail fd.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-4 W 1/4 corner
N.43°W. 55.22 Nail set SW side 8" tree
S.88°E. 36.3 Nail set N/S 24" Maple
S.35°W. 84.65 Nail set W/S 54" tree

I-5 SW corner
S.75°E. 78.12 Nail set N/S 54" tree
S.85°W. 111.89 Nail set N/S 48" tree
N.75°W. 136.37 Nail set S/S 40" tree

J-4 Center sec.
S.5°W. 44.83 Nail set E/S 8" tree
S.45°W. 7.1 Nail set E/S 4" tree
S.80°W. 7.18 Nail set N/s 4" tree

J-5 S 1/4 corner
N.5°E. 33.25 Nail set W/S 36" Oak
N.50°E. 33.15 Nail set S/S 36" tree
N.25°W. 22.0 Nail set E/S 40" Oak

K-5 SE corner,
S.20°W. 122.32 Nail set E/S tele pole
S.43°E. 32.45 Nail set W/S fence post
N.35°E. 110.71 Nail set W/S 48" tree

SIGNED BY Oscar Boss DATE 4-10-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY Oscar Boss DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

691

Form No. MLM735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.
FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

Aurelius Township, Ingham County

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 165

FILED

JUL 12 2 06 PM 19 74

REGISTER OF DEEDS

Ernest M. Lester

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY Sec. 2	T. 2 N., R. 2 W.	I-3, J-3
2. PROPERTY CONTROLLING IN SECTION ____	T. ____ N. S., R. ____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION ____	T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

I, Ronnie M. Lester do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram — over) were, in a field survey on May 10, 1974, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

I-3, Original Momument and Accessories Obliterated. Corner established and recorded as part of Subdivision of Long Acres as recorded in Liber 5, Page 53 of Ingham County records.

J-3, Original Monument and Accessories Obliterated.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-3, Found boatspike in accord with plat of Long Acres Subdivision as mentioned above. Corner falls in centerline of Aurelius and Columbia Roads.

J-3, Found boatspike in centerline of Columbia Road on old fence line North. Measurement East and West in close accord with original government measurement.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-3, SW Corner Section 2, T2N, R2W
Centerline 4" steel post, WSW, 130.57'
NE corner store at point 2.0' off of ground, SW, 72.90'
Nail & tag North side 28" walnut, SE, 77.14'

J-3, S 1/4 Corner Section 2, T2N, R2W
Steel fence post, NNE, 34.03'
1/2" bar, SSE, 32.72'
1/2" bar, NE, 66.89'

STATE OF MICHIGAN — RONNIE M. LESTER — LAND SURVEYOR — NO. 18998 — REGISTERED LAND SURVEYOR

SIGNED BY Ronnie M. Lester DATE May 16, 1974

SURVEYOR'S MICHIGAN REGISTRATION NO. 18998

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Form No. MLM735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 486

FILED

Nov 25 9 34 AM '75

REGISTER OF DEEDS

Ernie M. Lewis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 11	T. 2N N. S., R. 2W E. W.	K-3
2. PROPERTY CONTROLLING IN SECTION 11	,T. 2N N. S., R. 2W E. W.	2
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

I, George M. Young do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on October 24, 19 75, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19___ , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-3 Unknown

2 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-3 Found 1"iron pipe flush with asphalt

2 Set 1/2" Re-rod flush with asphalt (according to government Specifications)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 Nail & Cap in P.P. N 45° W 64.29'
Nail & Cap in T.P. S 35° W 74.91'
Nail & Cap in 24" Maple S 45° E 56.40'
Found 1" iron pipe flush with asphalt

2 Nail in Anchor post N 01° W 33.42'
Nail in T.P. S 03° W 30.18'
Top 12" C.M.P. @ c/l S 50° W 91.76'
Set 1/2" Re-rod flush with asphalt

STATE OF MICHIGAN
GEORGE M. YOUNG
LAND SURVEYOR
No. 17640
REGISTERED LAND SURVEYOR

SIGNED BY George M. Young DATE October 29, 1975

SURVEYOR'S MICHIGAN REGISTRATION NO. 17640 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

897

Form No. MLM735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

INGHAM COUNTY-AURELIUS TWP.

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 5 PG 54

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N. R. 2 W.	K-4
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

FILED

OCT 25 1 33 PM '78

REGISTER OF DEEDS

Paula Johnson

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Ronnie M. Lester, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April 26, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-4 Post set in original government survey by Harvey Parke, February, 1826
Corner referred to in miscellaneous Ingham County Suveyor records in a survey by W.H. Rayner, County Surveyor, November, 1867.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-4 Excavated a 10' x 7' hole to an average depth of 3.5' in the cneterline of Edgar Road on an extended fence line to the west and drain to the east. Found a ½" x 2' rerod with cap #17640 on the centerline of Edgar Road, on a fence line to the west and drain to the east, over a 1½" x 1' large pointed rock. Found 2 rake tongs, 1½" x ¼" x 18", in the center of a 2' pile of 4" to 8" rocks, 1' below the surface, on the centerline of Edgar Road and + 3.5' north of the extended fence line to west and drain to the east. Measured ± 2650' south to K-5 and + 2620' north to K-3. Accepted 2 rake tongs in rock pile as corner. Bar and cap #17640 removed per instructions R.L.S. #17640. Excavation conducted by Ingham County Survey and Remonumentation Project crew.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-4 E¼ Corner, Section 11, T2N-R2W
Set 4" x 36" concrete monument with ½" x 38" rerod with cap #18998 and concrete collar with cover in location of 2 rake tongs described above:
Nail & tag, #18998, west side 18" Wild Cherry, NE, 49.82'
Nail & tag, #18998, south side 6" Elm, West, 59.62'
Nail & tag, #18998, west side 18" Twin Maple, SE, 44.01'
Nail & tag, #18998, east side 20" Oak, SSW, 135.73'

SIGNED BY Ronnie M. Lester DATE 10/20/78

SURVEYOR'S MICHIGAN REGISTRATION NO. 18998

(SEAL) STATE OF MICHIGAN — RONNIE M. LESTER LAND SURVEYOR No. 18998 — REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY _____ DATE 10-23-78
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Director, Ingham County Survey and Remonumentation Project

(SEAL) STATE OF MICHIGAN — GARY D. LESTER LAND SURVEYOR No. 17624 — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 17624

1441

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET