K-8 SEC. 24

10-20-03

Fd ½" iron in base of 4"x6" fence post. Fence running Eastedly. 1 remaining witness tree remaining. Petroleum pipe line run through & destroyed fence running North. Dug 5' x 3' hole, Ex. bedrock numerous rocks, no further evidence of monumentation found. Set Aluminum cap & 3/4" iron pin Stamped "Higham County Surveyor" #3162.



Fd NAT in S. face 24" Oak #24-14

Set nail & tag in S. face 8" Oak

L-8 SEC 24 DT/JH 9/11/03

GONE, NO EVIDENCE. FALLS IN MIDDLE OF EXCAVATED GRAVEL PIT.

M-8 SEC. 24

Fd Painted Stone 18.2' South of fenceline running East. 5.7' East of old fence running West. Dug out old stone. Stone 18" long, surrounded by a cairn of stones. Removed stone found no other evidence of monument underneath. Accepted location of stone set by Drake as the position of the original location of the GLO monument replaced W/ 3/4" bar & cap stamped by Cr. Nelson P.S. 31253 and said point stone stood next to new monument

9/11/03 DT/JH



M-7 SEC. 24

Fd. ½" BLC #16053, 14.5' S. of ℄ M-36, in ℄ of March. Rd. Dug through 6" Pavement, Dug to 1.5' + rock bar, continued excavating to depth of 3' found no other evidence of monumentation. Set 3/4" bar & cap mon. dep. Stamped P.S. 31603.

9/11/03 DT/DH 4



Sec. 24 | L-7 | | N 1/4

Found 1/2" bar in ... mtn
Buried 1/2" bar ... depth of 3 ft.
Found 1/2" bar ... depth
Set Found no other evidence
of monument or marker bar
Stone pile in 1 foot ... mound
Set 3 pointers witness ...
B.T. 23.453. See ... bar
Caps in mon. box Stamped
P.J. 31603

9/11/03 | Drlr | 3



Sec 24 | K-7 | NW. 24

Fd 3/4" Pipe, 0.5' S. of
℄ of M-36 in N Edge Tree
line & Fence line S. Dug to 1.8'
removed 3/4" x 1.5' Pipe. Dug
to 3' to Dil which was clay/
Swamp mixed. Fand no other
evidence of monumentation.
Set 5/8" steel rebar w/
Cap stamped Indiana County/
Zephon PS 31603

DT/JH 7/8/03 2