


SOURCE: FOLDER #1 P. 18

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

Town 3 N. Range 2

Section No. 11



Section	Timber	Dist.	Bearing	Links	Section	Timber	Dist.	Bearing	Links
A	Aspen	1.4	N 61 E	66	K	Aspen	1.4	N 61 E	66
B	Aspen	1.4	N 61 E	66	L	Aspen	1.4	N 61 E	66
C	Aspen	1.4	N 61 E	66	M	Aspen	1.4	N 61 E	66
D	Aspen	1.4	N 61 E	66	N	Aspen	1.4	N 61 E	66
E	Aspen	1.4	N 61 E	66	O	Aspen	1.4	N 61 E	66
F	Aspen	1.4	N 61 E	66	P	Aspen	1.4	N 61 E	66
G	Aspen	1.4	N 61 E	66	Q	Aspen	1.4	N 61 E	66
H	Aspen	1.4	N 61 E	66	R	Aspen	1.4	N 61 E	66
I	Aspen	1.4	N 61 E	66	S	Aspen	1.4	N 61 E	66
J	Aspen	1.4	N 61 E	66	T	Aspen	1.4	N 61 E	66
K	Aspen	1.4	N 61 E	66	U	Aspen	1.4	N 61 E	66
L	Aspen	1.4	N 61 E	66	V	Aspen	1.4	N 61 E	66
M	Aspen	1.4	N 61 E	66	W	Aspen	1.4	N 61 E	66
N	Aspen	1.4	N 61 E	66	X	Aspen	1.4	N 61 E	66
O	Aspen	1.4	N 61 E	66	Y	Aspen	1.4	N 61 E	66
P	Aspen	1.4	N 61 E	66	Z	Aspen	1.4	N 61 E	66
Q	Aspen	1.4	N 61 E	66					
R	Aspen	1.4	N 61 E	66					
S	Aspen	1.4	N 61 E	66					
T	Aspen	1.4	N 61 E	66					
U	Aspen	1.4	N 61 E	66					
V	Aspen	1.4	N 61 E	66					
W	Aspen	1.4	N 61 E	66					
X	Aspen	1.4	N 61 E	66					
Y	Aspen	1.4	N 61 E	66					
Z	Aspen	1.4	N 61 E	66					

Run by the true meridian. Magnetic variation degrees 15 minutes W

Surveyed the 1st day of June 1887 by

County Surveyor of Ingham County, Michigan.

Sec. 11

18

LEROY
township

T 3 N. R 2 E

K-4

corner code attachment no.

13


p. 1 of 1

SOURCE: FOLDER #1 P. 19

TRANSCRIBED from ORIGINAL DUPLICATE on file at REMON. OFFICE

Town T. 3 N., Range 2 E.

1/4 line of Section No. 13 & 14



Sec.	Timber.	Diam.	Bearing.	Links.	Sec.	Timber.	Diam.	Bearing.	Links.
C	Center of Sec. 14 at intersection of 1/4 line				D	Round long blue ash for corner			
	Let shift iron with hinge with an					Round Pines	10	S 25° W	88 1/2
	up from old light wooden shaft					W Oak	6	N 68° E	47
	Willow	11	N 78° W	2 1/2		Anger	4	N 78° E	41
	Elm	8	N 45° E	2 00	A	Let for corner piece of carriage			
5	P. R. hwy	16	N 43° E	2 96		W. 1/2 in long			
6	O.P. and O.W.					Walnut	16	N 23° E	11 1/2
7	Let 1/2 gas pipe & flow also for corner								
	Stone for highway								
1	Cherry	14	N 66° W	2 1/2					
		14	S 66° E	35					
1	Round maple tree with small stone corner								
	Aspen	8	S 31° E	1 1/2					
	Anger	12	N 51° E	2 1/2					
		12	S 56° W	2 1/2					

Run by the true meridian. Magnetic variation 1 degrees minutes

Surveyed the 2, 3, 22 day of August, 1900, by

E. A. Callahan
Deputy County Surveyor of Ingham County, Mich.

Sec. 13 & 14

19

LEROY
township

T 3 N., R 2 E

I-6
corner code attachment no.


10 p. 1 of 1

SOURCE: FOLDER #1 P. 20

TRANSCRIBED from ORIGINAL DUPLICATE on file at REMON. OFFICE

Town 3 N, Range 2 E,

Section No. 13 & 14



Section	Timber	Area	Surveying	Links	Section	Timber	Area	Surveying	Links
1	Shrub, some willow	11	N 75° 45' W	21	1	Shrub, some willow	11	N 75° 45' W	21
2	R. P. from W. Oak	16	N 75° 45' W	296	2	R. P. from W. Oak	16	N 75° 45' W	296
3	O. P. O. H. S.	16	N 75° 45' W	296	3	O. P. O. H. S.	16	N 75° 45' W	296
4	Shrub, some willow	11	N 75° 45' W	21	4	Shrub, some willow	11	N 75° 45' W	21
5	Shrub, some willow	11	N 75° 45' W	21	5	Shrub, some willow	11	N 75° 45' W	21
6	Shrub, some willow	11	N 75° 45' W	21	6	Shrub, some willow	11	N 75° 45' W	21
7	Shrub, some willow	11	N 75° 45' W	21	7	Shrub, some willow	11	N 75° 45' W	21
8	Shrub, some willow	11	N 75° 45' W	21	8	Shrub, some willow	11	N 75° 45' W	21
9	Shrub, some willow	11	N 75° 45' W	21	9	Shrub, some willow	11	N 75° 45' W	21
10	Shrub, some willow	11	N 75° 45' W	21	10	Shrub, some willow	11	N 75° 45' W	21
11	Shrub, some willow	11	N 75° 45' W	21	11	Shrub, some willow	11	N 75° 45' W	21
12	Shrub, some willow	11	N 75° 45' W	21	12	Shrub, some willow	11	N 75° 45' W	21
13	Shrub, some willow	11	N 75° 45' W	21	13	Shrub, some willow	11	N 75° 45' W	21
14	Shrub, some willow	11	N 75° 45' W	21	14	Shrub, some willow	11	N 75° 45' W	21

Run by the true meridian. Magnetic variation 0 degrees 0 minutes

Surveyed the 23 day of August, 1900 by

E. A. C. C. C.
County Surveyor of Ingham County, Michigan.

Sec. 13 & 14

20


LEROY
township

T 3 N, R 2 E

I-6
corner code attachment no. 11 P. 1 of 1

SOURCE: FOLDER #2 P.15

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE



Section	Timber	Plum	Bearing	Links	Section	Timber	Plum	Bearing	Links
A	Stem				K	Stem & Limbs			
B	Stem								
C	Grass								
D	Stem & Limbs								
E	Grass								
F	Stem & Limbs								
G	Stem & Limbs								
H	Grass								
I	Stem & Limbs								

Run by the true meridian. Magnetic variation 0 degrees 10 minutes 6

Surveyed the 25 & 27 days of May 1900 by


John M. Gerson
County Surveyor of Lapeer County, Michigan

SOURCE: FOLDER #1 P. 36

TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at REMON. OFFICE

Town 3 N, Range 2 E

Section No. 2-3



Section	Timber.	Diam	Bearing	Links	Section	Timber.	Diam	Bearing.	Links
A	Beech	8	S. 51 E.	29					
	4	2.2	S. 12 1/2 E.	13					
B	Sugar	11	S. 41 W.	60					
	Beech	10	S. 15 1/2 E.	51					
C	Maple	12	N. 74 W.	7 1/2					
	Elm	15	N. 14 W.	21					
D	Beech	18	S. 67 W.	54 1/2					
	Sugar	26	N. 37 1/2 E.	54 1/2					

Run by the true meridian. Magnetic variation 2 degree 45 minutes. S.

Surveyed the 16 day of Dec 1863 by

County Surveyor of Ingham County, Michigan.

Sec. 23

36

LEROY
township

T 3 N, R 2 EW

I-7 12
corner code attachment no.

p. 1 of 1

TRANSCRIBED from ~~REDACTED~~ on file at REMON. OFFICE

Station	Corner.	Timber.	Bearing.	Links.	Station	Corner.	Timber.	Bearing.	Links.
A		Horsebush	S. 30 1/2. W	20 1/2					
"		Bush	S. 89. E	13					
B		W.D	N. 4. E	22					
"		"	S. 58 1/2. W	67					
B		"	S. 13 1/4. W	66					
"		Bush	S. 16. W	35 3/4					
D		"	N. 50. E	14 1/2					
"		"	S. 30 1/2. W	28					

C. Jackson

County Surveyor.

Var. $2\frac{1}{4}$ deg. min East

Liber *2* *Page* 178

Dec 17th 1853.

31

LEROY
township

T 3 N, R 2 EW


I-7 13
corner code attachment no.

p. 2 of 2

SOURCE: FOLDER #2 P.31

TRANSCRIBED from ~~REDACTED~~ on file at REMON. OFFICE


T. 3 N. R 2 E. Sec 23.



COUNTY SURVEYOR'S RECORD,

TOWN *Three* NORTH, RANGE *Three East*, MERIDIAN OF MICHIGAN.

SEC. *10*



TOWN *Three* NORTH, RANGE *Three East*, MERIDIAN OF MICHIGAN.

- Book 20 S 14 1/2 E 18*
 1 *DO 10 S 57 W 14*
 2 *Book 6 N 84 W 27*
 3 *DO 12 S 7 1/2 E 11 1/2*
 4
 5
 6
 7
 8
 9
 10 *Book 4 S 51 E 4 1/2*
 11 *Book 9 S 87 W 17*
 12 *Book 10 N 77 1/2 E 61*
 13 *Book 10 S 77 W 5-4*
 14
 15
 16
 17
 18
 19
 20
 21

24

25

INGHAM COUNTY, MICHIGAN.

359

TOWN *Three* NORTH, RANGE *Two East*, MERIDIAN OF MICHIGAN.


Run by the true Meridian N 2 3/4 E
Surveyed and Recorded June 12th 1864
By A. Jackson Co. Surveyor

Poplar 10 in S 77 E 13 lks } Being true to the center of Section 11. S 3 N R 2 E
Do 12 in S 48 W 24 lks } for H. Donner

SOURCE: FOLDER #2 P. 14

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

T 3 N. R. 2 E. Sec. 11



LEROY
township

T 3 N. R 2 E

K-4
corner code

14
attachment no.

p. 1 of 2

SOURCE: FOLDER #2 P. 14

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

Station	Corner	Timber	Bearing	Links	Station	Corner	Timber	Bearing	Links
A	Corner Pin	elm 21	N 68 E	66	G	Safe pipe	Ashtenut 18	N 44 E 1/2 S	78
B	Drag foot	elm 21	S 34 E	89	H	Safe pipe	elm 18	S 7 W	28
C	Drish	elm 8	S 72 W	39	I	Safe pipe	No timber		
D	east corner	elm 18	S 84 W	189	J	Safe pipe	No timber		
The above corner in the N.W. 1/4 of the					K	R.R. corner	W.O. 16	N 44 E	291.6
in the N.W. 1/4 of the section March 1889					The above corner in the S.E. 1/4 of the				
1889 Lib. 210					was established May 18th 1890				
L	6 Elm side	elm 8	N 72 W	34					
M	Apple	Apple 10	N 67 W	47					

John M. Eberhart County Surveyor

Var. D. deg. S. min.

Lib. S. Page 212

TRANSCRIBED from ~~REDACTED~~ on file at REMON. OFFICE

T. 3N. R. 2 E. Sec 23.

I-7

A. 8693 in 7992al B

Jones
No 697.

5.853.4 7943.0

LEROY
township

T 3 N, R 2 EW

I-7 corner code 14 attachment no.

p. 1 of 2

TRANSCRIBED from ~~XXXXXXXXXX~~ on file at REMON. OFFICE

SOURCE: RECORD OF CO. SURVEYOR V. 2 P. 172

TRANSCRIBED from ORIGINAL on file at REMON. OFFICE

172/1 1/2 E Sec 23
589 3/4 W 79 21
Bones
30 697
589 3/4 W 79 20 6


I-7
[A] Bush & S 36 27 1/2 Maple 12 N 7 1/4 W 7 1/2
[B] de 22 N 12 1/2 E 13 1/2 Elm 15 N 1/4 W 21
[C] Sugar 11 S 2 1/4 W 60 [D] Bush 18 S 37 1/2 W 32 1/2
[E] Bush 11 S 15 1/2 E 51 [F] Sugar 26 N 37 1/2 E 84 1/2
Run by the line Winona Ran. 2 1/2 E
Surveyed and recorded Oct 19th - 1853
by A. Buckner County Surveyor

Maple
de
Hon
Br
Run
Sugar
by

COUNTY SURVEYOR'S RECORD,

TOWN Three NORTH, RANGE Two East, MERIDIAN OF MICHIGAN.

SEC. 10



TOWN _____ NORTH, RANGE _____, MERIDIAN OF MICHIGAN.

- | | |
|----|---|
| 1 | 24 |
| 2 | 25 |
| 3 | |
| 4 | |
| 5 | |
| 6 | |
| 7 | |
| 8 | |
| 9 | |
| 10 | |
| 11 | } These lines are the 5 th 10 th from the R.R. South. |
| 12 | |
| 13 | |
| 14 | |
| 15 | |
| 16 | |
| 17 | |
| 18 | |
| 19 | |
| 20 | |
| 21 | |
| 22 | |
| 23 | |
- Title Don't Sugar 2 S 87° 46' W 37
 Title Don't Sugar 2 S 84° 46' W 49 1/2
 Title Adelbert Hickory 12 S 81° 2' 120
 Title R. H. B. 7 N 27 1/2° W 114 1/2
 Title N. E. Co. J. G. G.
 Title Alchuk Road S 83° W 115 1/4
 Title Elm 2 N 59 1/2° W 204
 Title Gaspere Sup W. D. 18 S 53° E 26
 Title Sup W. D. 20 N 28 1/4° E 148 1/2
 Title Elm 20 48° W 118

INGHAM COUNTY, MICHIGAN.

225

TOWN Three NORTH, RANGE Two East, MERIDIAN OF MICHIGAN.

Survey of S.E. Quarter of Sec 10 in T3N R2E. The survey shown in the plat given the distance and length of the lines chained and the bearings of the E & W quarter section line which was not chain but was run by compass to ascertain where the corrected line crossed the N & S quarter section line and the center was established at (13) and a tile corner planted and witnessed as represented in the descriptions at (13). As far as I can learn there were never any corner established at the point (13). The corner (23) was planted by Louis D. Preston while the witness stumps of the U. S. Survey were in existence. The corner (11) was established by him while the U. S. witnesses existed. U. S. Witness stump existed at (21), making a survey to my mind beyond any reasonable question of wrong or deficiency.

Surveyed by the true Meridian Var 15' East.

Mar 19th 1889

Peter S. Graham and Levi Alchin

Survey Chain men


John M. Cressy

Recorded, Mar. 22nd 1889.

Co. Surveyor.

COUNTY SURVEYOR'S RECORD,

TOWN Three NORTH, RANGE Two East, MERIDIAN OF MICHIGAN.



TOWN Three NORTH, RANGE Two East, MERIDIAN OF MICHIGAN.

- | | |
|----|---|
| 1 | 24 |
| 2 | 25 |
| 3 | 26 Iron pin. Clin of N 68° E 66 |
| 4 | 27 Drag tooth N.W. cor of same tract S 34° E 82 |
| 5 | 28 Brick Tame Cherry 3 S 72° W 30 |
| 6 | 29 Oak Iron Cherry 6 S 23° 3/4 E 65 |
| 7 | 30 Gas pipe Butternut 18 N 44° 58' E 73 |
| 8 | 31 Brick N.W. cor 18 S 7° W 225 |
| 9 | 32 Gas pipe No tree corner is 23 1/2 lbs and 8 R right of |
| 10 | 33 " " No trees |
| 11 | 2 |
| 12 | |
| 13 | |
| 14 | |
| 15 | |
| 16 | |
| 17 | |
| 18 | |
| 19 | |
| 20 | |
| 21 | Gas pipe No trees |
| 22 | |
| 23 | R.R. Iron N.W. 16 N 44° 3/4 E 29 1/2 |

INGHAM COUNTY, MICHIGAN.

227

TOWN Three North, RANGE Two East - MERIDIAN OF MICHIGAN.

Number 1803 the survey of 100 rods of land in the N.W. 1/4 of Section No 11 of T3 N R 2 E (Survey beginning at a point on the section line between section 10 and 11 32 rods S lks N by 3° 20' W from the quarter sec post on said section line and running thence N 3° 20' W 10 rods thence S 75 1/4° E 11 rods thence S 3° 21' E 11 rods to the center of Howell & Lansing plank Road now known as the Howell Road; thence N 75 1/4° W along the center of said road to the place of beginning where the section line crosses the center of said gravel road. The above described premises being the property of Peter & Graham at the time of date of this survey. Run by the true Meridian, Mar 19th 1889 Mag. Var established at 15' East. Recorded Mar 22nd 1889 Charles Chandler and Cluster Barber Sworn Chairmen

John M. Cress,
Co. Surveyor.


In survey No 1813 & 1814 the route 90 rods in width is divided and each parcel given 45 rods North & South and iron corner set. The lines (31) to (32) and (33) to (34) were run by the compass and corrected back stakes being driven every 40 rods. The corner (32) is on the section line between secs. 11 & 12 and 23 1/2 lks North of the R.R. rights of way

May 16th 1890 John M. Cress Co. Surveyor.

SOURCE: RECORD OF CO. SURVEYOR V. 3 P. 210

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

210



LEROY
township

T 3 N, R 2 E

K-4
corner code attachment no.

8
p. 1 of 2

SOURCE: RECORD OF CO. SURVEYOR V.3 P.210TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

Corner	Witness	Dist	Bearings	feet	Corner	Witness	Dist	Bearings	feet
to Section	to Sec	24 in	N 68° E	66	K R R corner	NO	16	N 4 3/4° E	291
B. Dry Tooth	R R corner of		S 34° E	82					
C. Brick	Barney Cherry	3 in	S 72° W	30					
D. Cat Run	Cherry	6 in	S 22 3/4° E	65					
Fully exposed	Brick	18 in	S 84 1/4° E	189					
E. Gas pipe	Butternut	18 in	N 44° 50' E	13					
F. Gas pipe	cherry	1.4	N 10° 55' E	130					
G. Brick	NO	18	S 7° W	225					
H. Gas pipe	no tree corner	18	23 1/2° N of R R right of way						
I. Gas pipe	No tree								
J. Gas pipe	No tree								

Number 1805 is the survey of one hundred rods of land in the N.W. 1/4 of Sec No 11 of T3N R2E. Survey Beginning at a point on the sec line between Secs 10 & 11 32 rods 15 Mts N by S 2° 20' W from the op sec post on said sec line and running thence N 5° 20' W ten rods thence S 75° 1/4° E ten rods thence S 5° 20' E ten rods to center of Howell and Lansing plank road now known as the gravel road thence N 75 1/4° W along the center of said road to place of Beginning where the section line crosses the center of said gravel road the above described premises being the property of Porter L. Graham at the time and date of this survey

Run by the true meridian March 19th 1889 the magnetic
var Estimated at 15° East Recorded March 22 and 1889

Charles Chamberlain & Chester Barber Surveyors

John M. Greary County Surveyor Tazewell Co. Ill.

In surveys No 1815 and 1814 the south 70 rods in width is divided and each parcel given 46 rods north and south and iron corners set the lines E to B and C to H were run by the compass and connected back station being driven every 40 rods The corner lies on the section line between Secs 11 & 12 and 23 1/2 Mts north of the R R right of way May 16th 1890 John M. Greary County Surveyor

LEROY
township

T 3 N, R 2 E


K-9
corner code attachment no.

8
p. 2 of 2

Doubleday Bros. & Co., Kalamazoo, 80365

Received for Record this _____ day of _____, A. D. 1_____, at _____ o'clock _____ M.
_____, Register of Deeds.

SECTION 14, Town 3 North, Range 2 East Meridian of Michigan.



13. C Drag tooth by bridge.

Section Corners.

1

2

3

4

9. 5 P. R. Iron 16" 74 3/4 E 296/lbs - SW. Cor. Barn N45°E 130/lbs.

5 8 Gas pipe Elm 6" N7W 22 lbs - Bitternut 4" S59½E 9 lbs - Maple 16" S40½E 37 lbs
4 9 Dr.

1/4 Posts on Section Lines.

10

11

12

13

14

15

16 Stone Oak 6" S 64 1/2 W 21 1/2 Bitternut S 89 1/4 W. 67 lbs.

MINUTES OF SURVEY [Concluded].

8 a *km.*
 b
 c
 14 d *km.*
 e
 f
 g
 h

1/4 Posts on 1/4 Lines.
 Centers of 1/4 Sections.


Corners 5-9-1-16 and d were found from
 former surveys and new witnesses made for the same.
 Corners a-e-8 were established and witnessed.

STATE OF MICHIGAN,

COUNTY OF INGHAM,


} ss.

I,



County Surveyor of said County.


Do Hereby Certify that I did, on the application of



Section 14 in the Township of La Roy, Town 2 North, Range 2 E
 Dec 11-12 1907 and the following persons acted as chainmen, first being duly sworn, to-wit:

Pastor Graham & John King

And I Further Certify that I have compared the foregoing copy with the original minutes made by me at the time of the survey, and that it is a full and true copy of the minutes of such survey, which minutes give the magnetic variation at the initial point of the survey.




County Surveyor.

SOURCE: RECORD OF CO. SURVEYOR V. 5 P. 52

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

COUNTY OF INGHAM, { ss. } at _____, Register of Deeds.

COPY OF MINUTES OF SURVEY.
SECTION 14, Town 3 North, Range 2 East Meridian of Michigan.



527/R L2

13.0 Drag loath by bridges.

(187)

SOURCE: RECORD OF CO. SURVEYOR V.5 P.52

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

52B/kL

3. 5 R. P. Lane 16" N43 1/4 E 296 1/2 - S.W. Cor. Barn N45 0 E 130 1/2.

8 Gaslight Elm 6" N77 W 22 lks - Return 4" S54 1/2 E - 9 lks - Maple 16" S40 1/2 E 37 lks

4 9 lks.

6 10 Stone Oak 6" S 64 1/2 W 21 lks Return 889 1/4 lks by lks.

V.5 P.52

LEROY
township

T 3 N, R 2 E W

I-6
corner code attachment no.

4
p. 2 of 4

SOURCE: RECORD OF CO. SURVEYOR V.5 P.52

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

527/R

IRON

Iron

V.5 P.52

LEROY
township

T 3 N. R 2 EW

I-6
corner code attachment no.

p. 3 of 4

SOURCE: RECORD OF CO. SURVEYOR V. 5 P. 52

TRANSCRIBED from RECORD OF CO. SURVEYOR on file at REMON. OFFICE

525
R

Corners 5-C-9-1-16 and d were found from
former surveys and new witnesses made for the same
Corners a-e-8 were established and witnessed

STATE OF MICHIGAN, } ss.
COUNTY OF INGHAM,

County Surveyor of said County.

Do Hereby Certify that I did, on the application of

R. R. Smith Jr.

R. R. Smith

Section 14 in the Township of Eastport survey

Town D North, Range 2 E

Dec 11-12 1907 and the following persons acted as chainmen, first being duly sworn, to-wit:

Garner Graham & John King

And I Further Certify that I have compared the foregoing copy with the original minutes made by me at the time of the survey, and that it is a full and true copy of the minutes of such survey, which minutes give the magnetic variation at the initial point of the survey.

County Surveyor.


R. R. Smith

7/4/11

V. 5 P. 52

COPY OF MINUTES OF SURVEY.

14 lines of
Parcel of land in Sections 13 & 14, Town 3 North, Range 2 E Meridian of Michigan



C. Center of Section 14 at intersection of 14 lines set shaft iron with hinge hole in top from old light wagon shaft. f.w. bears Willow 11 N. 9 1/4° W. 211 lbs and Elm 8 N. 4° E. 233 lbs.

5 R.R. Iron f.w. bears W. Oak 16 N. 4 1/4° E 296 lbs.

6. O.P.F. and C.W.S. set 3/4 gas pipe and plow shoe for corner.

7. Stone in highway f.w. bears cherry 14 N 56 1/4° W. 74 1/2 lbs.

8. Found Wagon tire with small stone around for bears

Bitternut 3. S. 31° E. 1 1/2 lbs
Do. 2. N 58° E. 2 1/2 "
Sugar 12. S. 46° W. 56 "

Found long blue stone for corner f.w. bears

Lombard poplar 10 S. 28° W. 88 1/2 lbs. 58.4
W Oak 6 N. 59° E. 47 "
Sugar. 4 N. 84 1/2° E. 41 " 27.1

A. set for corner. piece of Carriage tire 31 in long. f.w. bears
Walnut 6. N. 23° E. 118 1/4 lbs.

VOL 5. Pg 151

E A Calkins


August 1900

STATE OF MICHIGAN, RECEIVED FOR RECORD THIS 10/10/1914, at 10:00 O'CLOCK, A.M.
COUNTY OF INGHAM, Register of Deeds.

228

COPY OF MINUTES OF SURVEY.

1/4 line of Section 3, T. 3 N., R. 2 E., Meridian of Michigan.
Part of land in Section 3, T. 3 N., R. 2 E., Meridian of Michigan.



1517 1/2

229
 1
 5. Ceyster S. section 14 at intersection of 1st river set shaft iron with drum hole in top from old light wagon shaft. f.w. bears Willow 11 N. 93° W. 211 lbs and Elm 8 N. 4° E. 233 lbs.
 5 R.R. Iron f.w. bears W. Oak 16. N. 43° E 296 lbs.

6. Q.P.F. and T.W. S. Set 3 1/4 gas pipe and blow wire for coal.

7. Stone in highway f.w. bears Cherry 14 N 51 1/4° W. 74 1/2 lbs.
 Do. 14. S 66° E. 35 "

8. Found Wagon tire with small stone around for bears
 Bitternut 3. S. 31° E. 1 1/2 lbs
 Do. 2. N 58° E. 2 1/2 "
 Sugar 12. S. 46° W. 56 "

9. Found long blue stone for corner f.w. bears
 Lombard poplar 10 S. 28° W. 88 1/2 lbs.
 W Oak 6 — N. 59° E. 47 "
 Sugar. 4 — N. 84 1/2° E. 41 "

A. Set for corner. piece of Carriage tire 3 1/4 in. long. f.w. bears
 Walnut 6. N. 23° E. 118 1/4 lbs.

SOURCE: RECORD OF CO. SURVEYOR V. 5 P. 151

TRANSCRIBED from DUPLICATE on file at REMON. OFFICE

Magnetic Variation Less.

STATE OF MICHIGAN, }
COUNTY OF INGHAM, } ss.

Do Hereby Certify that I did, on the application of E. A. Lealkin Deputy, County Surveyor of said County,

14. Leroy Tp. Survey, 1/4 lines of Sections 13 and

Survey:

Section 2, in the Township of Leroy, Town 3, North, Range 2, E.
on August 2-3 and 22 and 23 1900, and the following persons acted as chainmen, first being duly sworn, to-wit:
Geo. Russell, Geo. W. Miller and Alpheus Leonard

And I Further Certify that I have compared the foregoing copy with the original minutes made by me at the time of the survey, and that it is a full and true copy of the minutes of such survey, which minutes give the magnetic variation at the initial point of the survey.

E. A. Lealkin Deputy, County Surveyor.

151 B/

V. 5 P. 151


LEROY
township

T 3 N, R 2 EW

I-6
corner code attachment no.

3
p. 3 of 3

Vol 5 P 261

SEC. 14

TOWN _____ NORTH, RANGE _____, MERIDIAN OF MICHIGAN.

- | | | |
|----|-----------------------------------|----|
| 1 | | 24 |
| 2 | | 25 |
| 3 | R.R. MOak 16" N 43° E 296 lks. | |
| 4 | Iron S.W. Corn Barn N 45° E 130 " | |
| 5 | | |
| 6 | Oak 6" S 64 1/2° W 21 lks | |
| 7 | Stone Bitternut S 89 1/4° W 67 " | |
| 8 | Iron. | |
| 9 | | |
| 10 | | |
| 11 | | |
| 12 | Drag Iron | |
| 13 | by Bridge | |
| 14 | Iron | |
| 15 | Gas pipe Elm 6" N 7° W 22 lks | |
| 16 | Bitternut 4" S 55 1/2° E 9 " | |
| 17 | Maple 16" S 40 1/2° E 37 " | |
| 18 | | |
| 19 | | |
| 20 | | |
| 21 | | |

INGHAM COUNTY, MICHIGAN.

TOWN 3 NORTH, RANGE 2 East, MERIDIAN OF MICHIGAN.

Survey of the N.W. 1/4 of Section 14 T3 N R2E for R. B. Smith Jr.
 Curtis Graham } Sworn
 John Ling } Chainmen.

Corners 3, 13, 4, 5, 6, and 14 were found from former surveys and new witnesses made for same. Corners 8, 7 and 15 were established and witnessed.

Surveyed Dec 11 and 12, 1907
 Recorded Jan 5, 1908

R. J. Pabb
 Co. Surveyor.

Vol 5

Le Roy
TOWN *Three* NORTH, RANGE *Two East*

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

69 (above cell 3)
227 (above cell 11)
261 (above cell 14)
210 (above cell 20)
257 (above cell 26)
117, 228 (above cell 32)
220 (above cell 33)
257 (above cell 35)

Locke
TOWN *Four* NORTH, RANGE *Two East*

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

40 (above cell 14)
19 (above cell 13)
26, 229 (above cell 20)
12, 223 (above cell 21)
41 (above cell 22)
39, 180 (above cell 23)
44 (above cell 24)
73, 182 (above cell 26)
78, 120 (above cell 33)
186 (above cell 35)
235 (above cell 36)