

26/25  
35/36

35/36

2527

LOCKE

LAND CORNER RECORDATION CERTIFICATE  
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 216 53

FOR CORNERS OF:- LOCATED IN:- CORNER CODE NUMBER  
1. PUBLIC LAND SURVEY 35 T. 4 S. R. 2 E. K-11, K-12  
2. PROPERTY CONTROLLING IN SECTION S. R. E.  
3. MISCELLANEOUS PROPERTY IN SECTION S. R. E.  
4. LOT NO. RECORDED PLAT  
5. PRIVATE CLAIMS

FILED

Aug 28 12 29 PM '72  
REGISTER OF DEEDS  
Paul M. Lewis  
MICHIGAN COUNTY, MICH.

CERTIFICATE

P.A.1970

3

FILED

Aug 28 12 29 PM '72

REGISTER OF DEEDS  
Paul M. Lewis  
MICHIGAN COUNTY, MICH.

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

P.A. 74, Michigan P.A. of 1970  
code diagram - over 1 were, in a  
1. re-monumented, recovered or  
required in the current manual  
management or by a decree of a  
bove were, in a field survey on  
expressed below and in con-  
or, by a Decree of a Court of

I, OSCAR BOSS do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970  
the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over 1 were, in a  
field survey on MAY 22 1972, established, re-established, monumented, re-monumented, recovered or  
restored as expressed below and in conformance with regulations and rules therefore as required in the current manual  
of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a  
court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on  
1972, found, recovered, restored, established or re-established as expressed below and in con-  
formance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of  
law:

A. Description of original monument and accessories and or subsequent restoration:

K-11 - UNKNOWN

K-12 - UNKNOWN

B. Description of corner evidence found and or method applied in restoring or re-establishing corner:

K-11 - P.K. SET - 2" IRON & FENCE SPLIT - SECTION SUBDIVISION

K-12 - P.K. SET - SECTION SUBDIVISION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-11 - P.K. SET  
N. 92° W. 26.4' 35" PIPE - FENCE POST BONE  
EAST 26.4' 35" PIPE - FENCE POST BONE  
K-12 - P.K. SET  
N. 64° E. 29.23' NAIL SOUTH SIDE 40" OAK  
S. 15° W. 115.65' NAIL EAST SIDE 40" OAK  
S. 17° E. 95.52' NAIL WEST SIDE 36" OAK

SIGNED BY Oscar Boss

DATE 8-23-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTRATION AND SURVEY

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO.

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER

2 PG 55

FOR CORNERS OF--

LOCATED IN--

CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 35 T. 4 N. 2 E.

I-13, J-13, K-13

2. PROPERTY CONTROLLING IN SECTION \_\_\_\_\_, T. \_\_\_\_\_ N. S., R. \_\_\_\_\_ E. W.

3. MISCELLANEOUS PROPERTY IN SECTION \_\_\_\_\_, T. \_\_\_\_\_ N. S., R. \_\_\_\_\_ E. W.

4. LOT NO. \_\_\_\_\_, RECORDED PLAT \_\_\_\_\_

5. PRIVATE CLAIMS \_\_\_\_\_

FILED

AUG 28 12 29 PM '72

REGISTER OF DEEDS

*Carol M. Lewis*  
HIGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, OSCAR BOSS do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on MAY 22 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

I-13 - UNKNOWN

J-13 - UNKNOWN

K-13 - UNKNOWN

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-13 - 1/2" IRON FOUND

J-13 - P.K. NAIL SET - SECTION SUBDIVISION

K-13 - P.K. NAIL SET - SECTION SUBDIVISION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-13 - 1/2" IRON FOUND  
WEST 54.14' NAIL NORTH SIDE TELEPHONE POLE  
S. 18° E. 88.6' NAIL WEST SIDE 30" MAPLE  
S. 10° W. 112.09' NAIL EAST SIDE 30" MAPLE

J-13 - P.K. NAIL SET  
N. 35° E. 12.25 NAIL WEST SIDE 54" OAK  
N. 65° W. 100.11' NAIL SOUTH SIDE 24" MAPLE  
S. 70° W. 58.4' NAIL NORTH SIDE 20" MAPLE

K-13 - P.K. NAIL SET  
N. 35° W. 48.2' P.K. WEST SIDE TELEPHONE POLE  
N. 13° E. 101.0' 1/2" BOLT WEST SIDE 30" OAK  
S. 71° E. 68.7' P.K. NORTH SIDE 48" ELM.



SIGNED BY Oscar Boss

DATE 8-23-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_

CHIEF OF SURVEY PARTY

DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

DATE \_\_\_\_\_

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

LOC 126

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER 1 PG 395

FILED

FOR CORNERS OF-- LOCATED IN-- CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 34 T. 4 N. R. 2 E. I-12, I-13

2. PROPERTY CONTROLLING IN SECTION .T. .N. S. R. E.

3. MISCELLANEOUS PROPERTY IN SECTION .T. .N. S. R. E.

4. LOT NO. . RECORDED PLAT

5. PRIVATE CLAIMS

MAR 27 1 56 PM '72  
REGISTER OF DEEDS  
Mia Bell Humphrey  
INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, OSCAR BOSS do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on JULY 20 1971, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:

I-12: UNKNOWN

I-13: UNKNOWN

B. Description of corner evidence found and or method applied in restoring or re-establishing corner:

I-12: SET: P.K. NAIL

EXIST'G OCCUPATION EVIDENCE  
IN RE-ESTABLISHING CORNER

I-13: FOUND 1/2" IRON

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-12: P.K. NAIL

N.W. - 64.4 - BLACK & WHITE HIGHWAY POST  
S.E. - 14.63 - NORTH LEG OF ARROW SIGN FD  
S.E. - 63.4 - POWER POLE ANCHOR POST FD  
S.W. - 93.3 - WEBBERVILLE RD. ROWLEY ST. SIGN GOVT  
S.W. - 103.9 - POWER POLE FD

I-13: 1/2" IRON

N.E. - 33.9 - STEEL STREET SIGN  
S.E. - 89.0 - 36" MAPLE  
S.W. - 113.3 - 36" MAPLE

SIGNED BY Oscar Boss

DATE March 10, 1972

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY CHIEF OF SURVEY PARTY DATE

APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR DATE

(SEAL)

Contn 35 LUCKY  
Contn 36

3108V  
LOCKE

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER 2 PC 119

FOR CORNERS OF— LOCATED IN— CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 35 & 36 T. 4 N. 2 E. J-12, L-12  
S. R. 1 E. 2

2. PROPERTY CONTROLLING IN SECTION T. N. S. R. E. W.

3. MISCELLANEOUS PROPERTY IN SECTION T. N. S. R. E. W.

4. LOT NO. RECORDED PLAT

5. PRIVATE CLAIMS

FILED

OCT 26 10 02 AM '72

REGISTER OF DEEDS

*Paul M. Lewis*  
INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on Oct. 7, 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and of subsequent restoration:

J-12, Unknown

L-12, Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-12, 1/2" Iron Set FENCE INTERSECTION

L-12, 1/2" Iron Set FENCE LINE OCCUPATION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-12, 1/2" iron

N. 15° W. 73.8 Nail East side 24" Poplar

S. 20° E. 17.25 Nail East side 6" Poplar

S. 83° E. 12.33 Nail South side 3" Poplar

L-12, 1/2" iron

S. 55° W. 22.50 Nail South side 20" Cherry

North 8.30 Nail West side 9" Oak

East 8.63 Nail North side 10" Maple

SIGNED BY Oscar Boss

DATE 10-23-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER 3 PG 113

FOR CORNERS OF-- LOCATED IN-- CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 35 T. 4 N. R. 2 E. J-11, K-11 I-11

2. PROPERTY CONTROLLING IN SECTION T. N. S. R. E. W.

3. MISCELLANEOUS PROPERTY IN SECTION T. N. S. R. E. W.

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

APR 16 AM 11 1974

JULIA S. JACKSON  
REGISTER OF DEEDS  
INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Oscar Ross do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram-over) were, in a field survey on August 16, 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

FILED

A. Description of original monument and accessories and/or subsequent restoration:

J-11 unknown  
K-11 unknown  
I-11 Unknown

APR 25 9 21 AM '74

REGISTER OF DEEDS

Paul M. Lewis  
INGHAM COUNTY, MICH.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-11 1/2" Iron set in hole of old fence post at the fence intersection  
K-11 1/2" Iron  
I-11 fd. 4" i-beam; set, 1/2" re-rod

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-11 NE Corner  
S. 80° W 13.89 ft. Nail S/S 8" Tree  
S. 62° W 12.17 ft. Nail S/S 6" Tree  
S. 17° E 24.63 ft. Nail W/S 6" Tree

I-11 NW CORNER, Sec. 35  
N. 83° W. 27.06 Nail S/S 28" tree  
S. 65° W. 33.92 Nail N/S 40" Maple  
S. 42° E. 28.0 Nail N/S 32" Maple

K-11 NE Corner  
N. 24° W 154.7 ft. Nail E/S power pole  
N. 85° W 61.15 ft. Nail N/S power pole  
N. 85° E 123.42 ft. Nail S/S power pole

SIGNED BY Oscar Ross DATE 4-10-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY Oscar Ross DATE 4-10-74

APPROVED AND SIGNED BY Oscar Ross DATE 4-10-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

Form No. ML 726  
DOUGLASS BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS