

SOURCE: General Land Office Maps Sheet #13

TRANSCRIBED from ~~ORIGINAL~~ on file at REMON. PROJECT
DUPLICATE

SURVEYOR'S NAME Harvey Parke

SURVEYOR NO. _____

DATE OF SURVEY March 1826


SECTION NO. 14, 15, 22, 23

MAGNETIC VARIATION _____

I-7 is 40.00 chs. from I-6.

Also I-7 is 40.00 chs. from I-8.

No written distances



VEVAY
TOWNSHIP

T2 N, R1 W

I-7
CORNER CODE

21
ATTACHMENT NO.

P. 1 of 1

SOURCE: G.L.O. Field Notes I-7 Page 40
 TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at Remonumentation PROJECT

40

North Between corners 22123
 2472 An Old 16m. 16m.
 4060 Set for sec. post for a
 2972 16m. N 3/4 W 2972
 Do 7m S 1/4 W 17
 6060 Corner Township
 6311 A 16m. 16m. 16m.
 * 6000 Set for post Co. Sec. 16. 15 22123
 I-7 2972 16m. N 1/4 E 15011
 Do 5m S 23 W 45
 Long corner 22123 Township

SOURCE: G.L.O. Field Notes I-7 Pg. 52
TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at Remonumentation Project

I-7

52

East- On a Random line between Sect 15 & 22
40.00 Set a lamp 2 1/4 Sec. post.
70.50 Enter Township
* 80.21 Int. A & S line 68 Ms. N. of Post
 ~~Corner of Sec. same as last mile.~~
West On the True line between Sect 15 & 22
19.26 A Lynn 9 in. diam.
40.10 1/2 Set 1/4 Sec. post. at over dist. w. a
 Beech 12 in. S 29 W 12 Ms.
 Sugar 8 in. N 45 1/2 E 19"
80.21 To Sec. Corner.

TRAVERSE POINT WITNESS REPORT

Traverse Point No. 4041

Tech. Sup'r. L. BRYAN

Township VeVay

Company PELAGIS

Recorded
Corner
Code H-7


Field Squad R. MARTIN #4

Date 2-7-78

N


Sketch and describe roads, monuments found or set, and witness established:

- 1) Fd. PK NAIL ON S. side of POWER POLE
S 20° E 27.07'
- 2) Fd. NAIL & TAG ON W. side of 36" OAK
N 15° E 36.65'
- 3) SET NAIL & TAG ON N. side of 36" MAPLE
S 60° E 70.45'



NOTE: USED PREVIOUS WITNESSES

OPEN
FIELD



Fd 5/8" REROD IN APPARENT E

TOMLINSON

GREY
HOUSE
1761

St. 1

DRIVE

WHITE
HOUSE
1747

0 #3

TRAVERSE POINT WITNESS REPORT

Traverse Point No. _____

Tech. Sup'r. LARRY B

Township ULUAY

Company POLARIS

Recorded Corner Code H-5

Field Squad #7 DAVE & CHRIS






Date FEB 8, 78



Sketch and describe roads, monuments found or set, and witness established:

- 1 S.E. CORNER OF HOUSE N.W. 85.65
- 2 SET N.Y.T. ON S/SIDE OF TWIN WILLOW W.N.W. 2510
- 3 " " " E/SIDE OF TRIP, MAPLE N. 44.86

H-5 IN BACK YARD OF #1738 DEXTER TRAIL



H-5 - FOUND 1/2 IRON BAR.



MONUMENTED CORNER REPORT

TECH. SUP'R. L. BRYAN TOWNSHIP VEVA
 COMPANY POLARIS CORNER CODE I-5
 FIELD SQUAD #9 MINSHALL RECORDED CORNER YES
 DATE 5.09.78 ROAD NAME EYES @ N-30

Sketch, witness, and describe monuments found, and location relative to traverse point and centerline of road.

N
 ED. 1/2" IRON ROD AS REC. BY RLS 18998 LIBER 1, PG. 537
 USED & CHECKED REC. WITHIN 10' OF ATTACHMENT

Q M-30


ED. 1/2" IRON AS REC.
 BY RLS 18998 IN
 Q OF RD.

Q EYES

SOURCE: Folder Set # 1 p. 7

TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at Remonumentation Project

FOR HEISEL




N-S 1/4 LINE
= 5313.0 (1848)
M-1984 = 5302.9

Sec.	Timber.	Diam.	Bearing.	Links.	Sec.	Timber.	Diam.	Bearing.	Links.
A	White Oak	10	N 70° E	11	A	White Oak	13	N 70° E	13.6
B	White Oak	10	S 50° E	13	B	White Oak	13	S 50° E	13.6
C	White Oak	10	N 70° E	13	C	White Oak	13	N 70° E	13.6
D	White Oak	10	S 50° E	13	D	White Oak	13	S 50° E	13.6
E	White Oak	10	N 70° E	13	E	White Oak	13	N 70° E	13.6
F	White Oak	10	S 50° E	13	F	White Oak	13	S 50° E	13.6
G	White Oak	10	N 70° E	13	G	White Oak	13	N 70° E	13.6
H	White Oak	10	S 50° E	13	H	White Oak	13	S 50° E	13.6

Run by the true meridian. Magnetic variation 3° degrees E minutes
Surveyed the 1st day of March 1898 by


J. J. Jackson
County Surveyor of Ingham County, Mich.

I-7 Richard W. STEADMAN #11370
Nov. 14, 1973



49

Off at Dec 4th of one at E. 10. Road made (under
 from a road to run to they have encroached on Sec 7. I made
 a survey of the 6th then 40 in 1866 & recorded it on page 50 of 2 book
 of survey. 3 in union with survey was 483
 G-4



NOTE: Rayner's note on side questions survey - claims encroachment on section #9 - Rayner survey on p. 3

Survey of the Northwest Quarter, and the North part of the Southeast Quarter of Section 12, T. 2 N. in Township No. Five North of Range No. One West, as represented by the accompanying Plat, the scale of which is Thirteen & a half chains to one inch, and in which the names of owners, amount of land owned by each, the bearing and distance of lines, letters of reference to lines and corners, and the position of Roads &c. are respectively given. Road lines drawn with red ink.

The corners of the Survey are described as follows:

A = a stone 30 inches long, 24 inches in ground = the corner.

B = a Post from which an Elm 10 inches diameter bears S. 62° E. 90 1/2 links

C = a Post " " a Sugar 28 " " N. 21° E. 27 "

D = a corner of a former Deed of 62.75 acres now obsolete.

E = a Post from a Beech 16 inches diameter bears S. 45° E 10 "

F = a Post in the Highway no bearing Trees marked.

G = a Post from which a Beech 9 inches diameter bears S. 61° E 10 "

H = a Post in the Section line no bearing Trees, also at

I K L M are Posts, and N with D is out of use (obsolete)

O = a Stone appropriately marked for corner

P = a Post from which a Sugar 5 inches diameter bears S. 37° E 60 1/2 "


" " " " Sugar 8 " " N. 73° E 78 1/2 "

Application for this Survey made by Wilson B. Hicks

Given by the true Meridian Magnetic Variation = 2 1/4° E.

Surveyed April 3rd & May 4th 1869 and Recorded Feb 24th 1870.

by J. J. Brown Dep. County Surveyor for Ingham County Mich.



I-7

VEVAY
township

T 2 N, R 1 SW


I-7
corner code attachment no.

p. 1 of 1

(over PLEASE)

Town 2 N., Range 1 W.

Section No. 22




Sec.	Timber.	Diam.	Bearing.	Links.	Sec.	Timber.	Diam.	Bearing.	Links.
A	oak	2	S 45° E	1.41					
B	oak	10	N 12° E	1.19					
C	maple	10	N 79° E	5.4					
D	m -	10	S 83° E	2.86					

Run by the true meridian. Magnetic variation degrees minutes
 Surveyed the day of 190... by
H. H. R.
 County Surveyor of Ingham County, Mich.

Sec. 22

SOURCE: FOLDER SET #1 p. 9
TRANSCRIBED from ~~ORIGINAL~~ on file at Remon, OFFICE
DUPLICATE

Section No. 10



Sec.	Timber.	Diam.	Bearing.	Links.	Sec.	Timber.	Diam.	Bearing.	Links.
X	B. Walnut	3	N 28 E	262	A	Long	3	S 97 E	72
	Apple	2	N 41 E	69		2	1	N 50 E	9
X	Long	24	S 64 E	264	B	1/2 R	6	S 30 E	210
	Buck	6	N 73 E	33		2	1	71	
1	B. Cherry	20	S 64 N	90	C	Long	2	N 26 E	47
	Elm	10	N 46 N	35		2	1	N 55 E	43
2	Elm	10	S 37	64		2	1	N 47 E	76
	Maple	10	N 71 E	41 1/2		2	1	N 50 E	150
3	O. H. O.	4	S 27	29		1	1		
	Long	1	S 62 E	28					
4	Long	3	N 46 E	92 1/2					
	B. Walnut	8	S 39 E	141 1/2					
5	Apple	1	N 70 E	84 1/2					
	B. Oak	8	S 71 E	264 1/2					
3	N. A. original	8	N 71 E	264 1/2					
	O. A.	8	N 71 E	264 1/2					

Surveyed the 9 day of May 1866 by

W. H. Raper
County Surveyor of Ingham County, Mich.

Sec: 10

VEVAY
township

T 2 N, R 1 EW


4-4 corner code, 5 attachment no.

p. 1 of 1

9

T. 2 N. R. 1 W.

Section 10



VEVAY township

T 2 N, R 1 W

H-4 4 corner code attachment no.

p. 1 of 1

(OVER PLEASE)

Survey of the South-east quarter of Section No Ten in Township No Six North of Range No One West, as shown by the plat by which the bearings and distances of the lines surveyed, and letters of reference to lines and corners are respectively given.

The center corner A was established at the intersection of the East & West quarter post line, with the North & South quarter post line, heretofore established by J. J. Brown, in 1869 (see Page 49). (see attach #3)

The corners are described as follows:

Corner.	Witness.	Dia.	Bearing.	Links.	Corner.	Witness.	Dia.	Bearing.	Links.
A = Post	Elm	10	N. 42 1/2° E	132	C = Post	Bitternut	6	N. 87 1/2° E.	61 1/4
" "	Bitternut	10	S. 2 1/2° E	133	" "	"	9	N. 31° E.	75 1/2
B = "	Beech	30	S. 42 1/2° E.	41	D = Stone	Apple tree	6	N. 70° E.	84
" "	W. Ash	24	S. 3° E	39	E = Post	no trees marked			
					F = "	Elm	8	N. 81° E.	26

Run by the County Meridian Vari 10° 20' East

Surveyed March 17th 1882

By A. P. Drake

Recorded April 3rd 1882

Co. Surveyor

NOTE: T. J. BROWN SURVEY (attach #3) does not establish center.

SOURCE :

Folder Set #2

p. 26

TRANSCRIBED from ~~ORIGINAL~~ on file at Remonumentation Project
DUPLICATE



O. L. Carl
No. 488

GF10

West 1624 19

F. Davis
No. 484

(over please)

VELAY
township

T 2 N, R 1 W

G-4

corner code attachment no.

21

p. 1 of 1

Station	Corner	Timber	Bearing	Links	Station	Corner	Timber	Bearing	Links
A		Hint 10	N. 24. E	17					
		W.D. 10	S. 60. W	9					
B		Eng 28	N. 21. E	27					
		Iron 6	S. 37. W	9					
C		Bush 16	S. 44. E	10					
		" 14	S. 44. W	26					
D		" 9	S. 61. E	10					
		Lynn 16	N. 3. W	41					
E		Tom 8	S. 22. E	58					
		" 6	N. 6. E	7 1/2					
F		W.G. 10	S. 67. W	29 1/2					
		Bush 5	S. 64. E	6					

E. Jackson


County Surveyor.

Var. 3 deg min East

Liber 2 Page 51



March 6th 1849.

NO WITNESSES



W. B. Adams 1888 28' W 59 1/4 Sec 14 1/4 Sec 15 1/4 Sec 16 1/4 Sec 17 1/4 Sec 18 1/4 Sec 19 1/4 Sec 20 1/4 Sec 21 1/4 Sec 22 1/4 Sec 23 1/4 Sec 24 1/4 Sec 25 1/4 Sec 26 1/4 Sec 27 1/4 Sec 28 1/4 Sec 29 1/4 Sec 30 1/4 Sec 31 1/4 Sec 32 1/4 Sec 33 1/4 Sec 34 1/4 Sec 35 1/4 Sec 36 1/4 Sec 37 1/4 Sec 38 1/4 Sec 39 1/4 Sec 40 1/4 Sec 41 1/4 Sec 42 1/4 Sec 43 1/4 Sec 44 1/4 Sec 45 1/4 Sec 46 1/4 Sec 47 1/4 Sec 48 1/4 Sec 49 1/4 Sec 50 1/4 Sec 51 1/4 Sec 52 1/4 Sec 53 1/4 Sec 54 1/4 Sec 55 1/4 Sec 56 1/4 Sec 57 1/4 Sec 58 1/4 Sec 59 1/4 Sec 60 1/4 Sec 61 1/4 Sec 62 1/4 Sec 63 1/4 Sec 64 1/4 Sec 65 1/4 Sec 66 1/4 Sec 67 1/4 Sec 68 1/4 Sec 69 1/4 Sec 70 1/4 Sec 71 1/4 Sec 72 1/4 Sec 73 1/4 Sec 74 1/4 Sec 75 1/4 Sec 76 1/4 Sec 77 1/4 Sec 78 1/4 Sec 79 1/4 Sec 80 1/4 Sec 81 1/4 Sec 82 1/4 Sec 83 1/4 Sec 84 1/4 Sec 85 1/4 Sec 86 1/4 Sec 87 1/4 Sec 88 1/4 Sec 89 1/4 Sec 90 1/4 Sec 91 1/4 Sec 92 1/4 Sec 93 1/4 Sec 94 1/4 Sec 95 1/4 Sec 96 1/4 Sec 97 1/4 Sec 98 1/4 Sec 99 1/4 Sec 100

SOURCE: Collection OF VARIOUS SURVEYS Pages 21½ + 22½
 TRANSCRIBED from ORIGINAL on file at Remonumentation Project
DUPLICATE



VEVAY
township


T 2 N, R 1 W

I-7
corner code

5
attachment no.

p. 1 of 1

SOURCE: Record of the I.C.S. Vol. 3 Page 83 Yr. 1874
TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at REMON. PROJECT



VEVAY
township

T 2 N, R 1 W

I-7
corner code

8
attachment no.

p. 1 of 1

(PLEASE PRINT)

A = a stone 2 ft. long set with a point designated it overlaid for corner.

" = " " " " Beach 15 " " S. 11° W. 60% " " (New

• " " " " Bush 14 " " " " S. 82 3/4° E. 27 "

E. No. 1

Note: The corners marked A, B, & F & D, are described according to the resurvey made May 30th 1874 by.

J. J. Brown Co. Surveyor of Ing. Co. Mich.


10-1-1 8 T-1 10-1-1 10-1-1

SOURCE: Record of the I. C. S. Vol. 1 Page 28 Yr. 1839

TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at Remon. Project

I

-7



VEVAY
township

T 2 N, R 1 W

I-7
corner code

9
attachment no.

p. 1 of 1

(OVER PLEASE)

I-7

*

A Jam 9 in S 23 N 45 lbs
Jam 5 in S 23 N 45 lbs

B Jam 25 in S 27 N 6 2 lbs
Black 7 in S 25 N 13

C Maple 10 in S 21 N 23 lbs
Jam 24 in S 28 N 61 lbs

D W Oak 18 in S 21 N 18 lbs
Lepin 20 in S 24 N 69 lbs

E Elm 14 in S 21 N 24 lbs
Horn 9 in S 20 N 84 lbs

F W Oak 30 in S 51 N 57 lbs
Lynn 14 in S 17 N 18 lbs

G Jam 24 in S 26 N 42 lbs
Black 10 in S 47 N 2 lbs

H W Oak 24 in S 28 N 32 lbs
W Oak 24 in S 28 N 32 lbs

I Sugar 16 in S 21 N 28 lbs
Sugar 7 in S 11 N 17 lbs


J Black 12 in S 25 N 5 lbs
Black 16 in S 34 N 16 lbs

K Black 16 in S 45 N 11 lbs
Elm 20 in S 66 N 2 lbs

W Oak 16 in S 21 N 18 lbs
W Oak 12 in S 46 N 2 lbs
Run by the Iron Mountain Van. & Co.
Sawy Wood used from June 1 1857
by A. Jackson & Co. for
the County of Lyndebury

(OVER PLEASE)

TRANSCRIBED from ~~ORIGINAL~~
DUPLICATE on file at REMON. OFFICE



VEVAY
township


T 2 N, R 1 EW

I-7
corner code attachment no. p. 1 of 1

10
attachment no.

p. 1 of 1

(OVER PLEASE)



I-7

VEVAY
township

T 2 N, R 1 W

I-7
corner code

12
attachment no. p. 1 of 1

(over PLEASE)

Re-Survey of the Northwest Quarter of Section No Twenty-three in Town-
ship No Two North of Range No One West, as seen in the accompanying
Plan. The corners are described as follows:

- * A = a stone two and a half feet long and tapering to about three inches square, set
small end up and top cross-marked about even with the surface the corner
point, from which a Maple thirteen inches diameter bears S. 84 1/4° W. 23 1/2' and
B = a Post from which a Cherry eighteen inches diameter bears N. 21 1/2° E. 38 1/2' and
C = a Post " " a Lynn Twenty four " " " " N. 69° W. 47' "
" " " " a Lynn Twelve " " " " N. 22° W. 25 1/2' "
H " " " a Beech Eight " " " " S. 87 1/4° W. 7' "
" " " " a W. Oak Twenty four " " " " S. 28 1/2° E. 39' "

I a Stone set in the ground even with the surface. No Trees

Note: - In this Re-survey the original trees marked at the corners
are retained so far as they were found, but where they were gone,
new ones were marked & noted where they stood convenient.

Surveyed May 30th 1874. Magnetic var. 1° 55' E

J. J. Brown County Surveyor for Morgan County, Miss.

Remarks

The Corner A was lost, and re-established in this survey by means
of monument and intersections. This was done by surveying from the known
Corner (K) through the known corners I & O, a straight line to intersect A & at d.
Where the lost corner (A) was re-established: May 30th 1874 by

J. J. Brown Co Surveyors

H. Buck 11 at 64 W. 26 1/2 lbs
 B. Oak 36 in N 86 W. 28 lbs
 B. Buck 16 in S 18 W. 37 lbs
 C. Gym 14 in N 75 W. 36 lbs
 B. Buck 3 in at 64 1/2 E. 4 lbs
 * D. Sugar 24 in at 65 1/2 E. 37 1/2 lbs
 B. Buck 22 in at 81 W. 17 lbs
 C. Buck 18 in west 15 lbs
 C. Gym 14 at 63 E. 10 lbs
 J. Sugar 18 S 26 1/2 W. 38 lbs
 J. Sugar 24 S 74 E. 44 1/2 lbs
 Run by the true meridian Var 3' 10" E
 Surveyed and recorded March 9 1843
 by A. Jackson Surveyor

In Gov notes the trees are
just reversed.

I-7

on 12-12-12

(over please)

12-12-12


VEVAY

10 Beech 11 at 87 1/4 W. 26 1/2 lbs
 11 Oak 30 in at 86 W. 28 lbs
 12 Beech 16 in S 18 W. 37 lbs
 13 Gum 14 in at 75 W. 31 lbs
 14 Beech 30 in S 64 1/2 E. 4 lbs
 * 15 Sugar 24 in S 65 1/2 E. 31 1/2 lbs
 16 Beech 22 in S 81 W. 17 lbs
 17 Beech 18 West 15 lbs
 18 Gum 14 at 63 E. 10 lbs
 19 Sugar 18 S 26 1/4 W. 38 lbs
 20 Sugar 24 S 77 1/4 E. 44 1/2 lbs
 Run by the true Meridian Van 3 10 E
 Surveyed and corrected March 9 1843
 by A Jackson. Observer

(EXAMPLE)

Town 2 N., Range 14 W.

Section No. 14



Sec.	Timber.	Diam.	Bearing.	Links.	Sec.	Timber.	Diam.	Bearing.	Links.
A	Asch	6	N 72° 30' E	200	H	Asch	14	S 47° 30' N	88 1/2
B	Asch	8	N 72° 30' E	182	I	Asch	14	S 53° 30' E	90 1/2
F	Cherry	20	S 18° E	29 1/2	J	Asch	24	S 68° 30' N	41 1/2
G	Maple	4	S 52° 30' W	62	K	Asch	10	S 75° 30' E	24
H	Maple	18	N 18° E	33 1/2	L	Asch	10	S 75° 30' E	24
I	Maple	6	N 72° 30' E	200	M	Asch	10	S 75° 30' E	24
J	Maple	4	S 18° E	29 1/2	N	Asch	10	S 75° 30' E	24
K	Maple	12	S 52° 30' W	62	O	Asch	10	S 75° 30' E	24
L	Maple	12	S 52° 30' W	62	P	Asch	10	S 75° 30' E	24
M	Maple	12	S 52° 30' W	62	Q	Asch	10	S 75° 30' E	24
N	Maple	12	S 52° 30' W	62	R	Asch	10	S 75° 30' E	24
O	Maple	12	S 52° 30' W	62	S	Asch	10	S 75° 30' E	24
P	Maple	12	S 52° 30' W	62	T	Asch	10	S 75° 30' E	24
Q	Maple	12	S 52° 30' W	62	U	Asch	10	S 75° 30' E	24
R	Maple	12	S 52° 30' W	62	V	Asch	10	S 75° 30' E	24
S	Maple	12	S 52° 30' W	62	W	Asch	10	S 75° 30' E	24
T	Maple	12	S 52° 30' W	62	X	Asch	10	S 75° 30' E	24
U	Maple	12	S 52° 30' W	62	Y	Asch	10	S 75° 30' E	24
V	Maple	12	S 52° 30' W	62	Z	Asch	10	S 75° 30' E	24
W	Maple	12	S 52° 30' W	62					
X	Maple	12	S 52° 30' W	62					
Y	Maple	12	S 52° 30' W	62					
Z	Maple	12	S 52° 30' W	62					

Run by the true meridian. Magnetic variation _____ degrees _____ minutes
 Surveyed the _____ day of _____ 1900 by _____

John H. Payne
 County Surveyor of Ingham County, Mich.

Sec. 14

EVAY
 township


T 2 N., R 14 W.

I-7

corner code

19
 attachment no.

p. 1 of 1



Section	Timber	Dist	Bearing	Links	Section	Timber	Dist	Bearing	Links
A	elm	23	to top	83	G	Hick	10	N. 24 E.	17
B	maple	3	S. 63 W. 1207			W. Oak	10	S. 40 W.	3
C	elm	6	S. 64 W.	52		Sugar	20	S. 17 E.	27
D	Sugar	20	S. 42 E.	116	B	Sugar	28	S. 15 E. W.	132
		4	S. 84 W.	74			5	N. 7 E. W.	73 1/2
		2	S. 22 E.	74			3	N. 65 E.	24
					C	Sugar	3	N. 2 E.	63
						elm (bush)	7	S. 25 W.	10
						Sugar	16	N. 3 W.	41
						Rack	9	S. 61 E.	10
						Oak	6	N. 18 E.	18 48

Run by the true meridian, Magnetic variation degrees minutes W.
 Surveyed the 24 day of Jan 1866 by
W. H. Rymer
 County Surveyor of Ingham County, Michigan.

NO WITNESSES


T 2. N

R 1 W

15

P 9.

103



Hick 9 in S 35 W 20 lbs
 Beech 15 in N 74 E 23 1/2 lbs
 Beech 6 in S 74 1/2 W 18
 do 8 in S 79 E 22
 Sugar bin S 12 1/2 E 14
 do 12 N 3 1/2 W 27
 Jam 9 N 19 E 150
 Sugar 5 S 90 W 11
 Sugar 12 S 80 E 26
 Beech 12 S 29 W 12
 Sugar 8 N 45 1/2 E 19

Run by the true Meridian Van 3 1/6 E
 Surveyed & Recorded Jan'y 19 1846
 by A Jackson Co Surveyor

O & D were Rewitnessed by W. H. Baynes
 Deputy Co. Surveyor April 9th 1870