SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

INGHAM

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 450

FILED

SEP 24 1 43 PM '75

REGISTER OF DEEDS

Ernest M. Lewis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	11 T 2 N R 2 E	J-5 K-5
2. PROPERTY CONTROLLING IN SECTION	T N R E	
3. MISCELLANEOUS PROPERTY IN SECTION	T N R E	

4. LOT NO. ..... RECORDED PLAT .....

5. PRIVATE CLAIMS .....

I, James A. Porter, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on August 13, 19 75, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ..... 19 ..., found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Original Post & Witnesses destroyed. Original Post & Witnesses destroyed.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Found 3/4" pipe, Raised to surface with #4 rerod and cap.

Found Railroad Spike in intersection of Iosco and Brogan Roads.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Witnesses to #4 rerod:
Nail & Tag in SW Cor Railroad Tie Fence Corner North 15.23 feet
Nail & Tag in 18" Twin Cherry NE 28.85 feet
Nail & Tag NE Cor 1-Story Shed SW 48.45 feet

Left in place with the following witnesses:
Nail & Tag in 28" Cherry ENE 81.08 feet
Nail & Tag in 28" Maple ESE 81.55 feet
Nail & Tag in 18" Maple SSE 96.47 feet

SIGNED BY James A. Porter DATE August 21, 1975

SURVEYOR'S MICHIGAN REGISTRATION NO. 19003

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ..... CHIEF OF SURVEY PARTY DATE .....

APPROVED AND SIGNED BY ..... MICHIGAN REGISTERED LAND SURVEYOR DATE .....

STATE OF MICHIGAN JAMES A. PORTER LAND SURVEYOR No. 19003 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. .....

876 Form No. MLM735 DOUBLEDAY BROS. & CO., SALAMANCA, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 29, 1971 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township T 2 N, R 2 E/W K-5 corner code 1 attachment no. p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 529

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 13 T 2 N R 2 E		K-5, L-5, L-6,
2. PROPERTY CONTROLLING IN SECTION T S, R E		
3. MISCELLANEOUS PROPERTY IN SECTION T S, R E		
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

FILED

Feb 3 8 39 AM '76

REGISTER OF DEEDS

Grant M. Lewis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on 8-7 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19 found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-5 Unknown
~~L-5~~ Unknown
L-6 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-5 RR Spike
~~L-5~~ ½" Iron
L-6 Iron set

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-5 NW Corner
S 22°W 75.39 Nail W/S 32" Oak
S 10°E 52.23 Nail W/S Telephone pole
S 75°E 96.11 Nail W/S 18" Maple

L-6 Center Section
N 0.91 Nail W/W 20" Hickory
W 8.55 Nail W/S 10" Oak
S 9.83 Nail S/S ~~20"~~ Oak 20"

L-5 N¼ Corner
S 33°E 32.77' SW side 14" Tree (Hickory)
N 3° E 68.50' E side 14" Oak
N 55°E 80.15' NW side 14" Oak

SIGNED BY Oscar Boss DATE 1-22-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (CHIEF OF SURVEY PARTY) DATE _____

APPROVED AND SIGNED BY _____ (OFFICIAL OF STATE OR UNITED STATES OFFICE) DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

927

Form No. 66.M730 (Lansing, Mich. B Co., 66,000,000, 1970)

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 29, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township T 2 N, R 2 E/W K-5 corner code 2 attachment no. p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 531

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 13	T. 2 N. R. 2 E.	K-6, K-7, L-7
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

FILED

Feb 3 8 39 AM '78

REGISTER OF DEEDS

Ernest M. Lewis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on 8-7 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ..... 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-6 Unknown
K-7 Unknown
L-7 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-6 ½" Iron
K-7 ½" Iron
L-7 ½" pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-6 W¼ Corner
S 59°W 31.02' Spike in NW side 24" Oak
N 71°W 21.07' Spike in N side 22" Oak
S 43°E 42.61' Spike in SW side 18" Hickory

L-7 S¼ Corner
N 2°E 27.3 P.K.Nail E/S 20" Tree
S 65°W 39.3 Nail S/S 26" Oak
S 21°E 21.41 Lg. Nail E/S 10"Tree

K-7 SW Corner
N 53°W 38.95 Spike in E side Tele pole
N 40°E 47.39 Spike in SE side 36" Tree
S 43°W 31.35 centerline Street sign pole

SIGNED BY Oscar Boss DATE 1-29-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

928 Form No. ML M730 POUDLEY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township T 2 N, R 2 E W K-6 corner code 1 attachment no. p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF—:	LOCATED IN—: White Oak Twp	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N. R. 2 E. W.	L-5, K-6
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	

4. LOT NO. ..... , RECORDED PLAT .....

5. PRIVATE CLAIMS .....

LIBER 4 PG 72

FILED

Jun 30 11 43 AM '77

REGISTER OF DEEDS

Ruth Johnson

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Karol R. Piotrowski, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 5, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ..... , 19 ..... found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law.

A. Description of ~~original monument and accessories and or~~ subsequent restoration:

K-6 ½" Re-rod 6" deep
L-5 ½" Re-rod

B. Description of corner evidence found ~~and/or marked applied or restoring or re-establishing same~~:

K-6 Found ½" re-rod 6" deep
L-5 Found ½" re-rod

C. Description of monument (or corner) and accessories established to perpetuate locating the position of the corner.

K-6 N85°W 20.8' to 24" Oak
S45°E 42.43' to 20" Hickory
S60°W 30.7' to 24" Oak

L-5 N45°E 47.75' to 10" Oak
NORTH 24.60' to 2" Pipe in center of stone pillar
S70°E 76.76' to 15" Nut tree

SIGNED BY Karol R Piotrowski DATE 6-5-75

SURVEYOR'S MICHIGAN REGISTRATION NO. 9685

STATE OF MICHIGAN — KAROL R. PIOTROWSKI — 9685 — REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ..... DATE .....
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY ..... DATE .....
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. .....

1074

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION JAN. 29, 1971
REVISED MAY 14, 1970

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

WHITE OAK township — T 2 N, R 2 E/W — K-6 corner code — 2 attachment no. — p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL / ~~DUPLICATE~~ on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970 *(AS AMENDED)

LIBER 3 PG 531

FILED

FEB 3 8 39 AM '78

REGISTER OF DEEDS
Ingham County, Mich.

REGISTER OF DEEDS STAMP AND FILING NUMBER

FOR CORNERS OF—: LOCATED IN—: CORNER CODE NUMBER

1. PUBLIC LAND SURVEY 13 T 2 N. R 2 E. — K-6, K-7, L-7
2. PROPERTY CONTROLLING IN SECTION ___ T ___ N. S. R. ___ E. W.
3. MISCELLANEOUS PROPERTY IN SECTION ___ T ___ N. S. R. ___ E. W.
4. LOT NO. ___ RECORDED PLAT ___
5. PRIVATE CLAIMS ___

I, Oscar Boss, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on K-7 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ___ 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-6 Unknown
K-7 Unknown
L-7 Unknown

B. Description of corner evidence found and, or method applied in restoring or re-establishing corner:

K-6 1" Iron
K-7 1" Iron
L-7 1" pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-6 W¼ Corner
S 59°W 31.02' Spike in NW side 24" Oak
N 71°W 21.07' Spike in N side 22" Oak
S 43°E 42.61' Spike in SW side 18" Hickory

L-7 S¼ Corner
N 2°E 27.3 F.K.Nail E/S 20" Tree
S 65°W 39.3 Nail S/S 26" Oak
S 21°E 21.41 Lg. Nail E/S 10"Tree

K-7 SW Corner
N 53°W 30.95 Spike in E side Tele pole
N 40°E 47.39 Spike in SE side 36" Tree
S 43°E 81.35 centerline Street sign pole

SIGNED BY Oscar Boss DATE 1-29-74

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ___ DATE ___
(State or County Agency)

APPROVED AND SIGNED BY ___ DATE ___
(State or Registered Land Surveyor)

SURVEYOR'S MICHIGAN REGISTRATION NO. ___

928 Form No. 555-0728 Hugh Gray Wood, S. Co., Kalamazoo, Mich.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, APR. 29, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township T 2 N, R 2 E/W K-7 corner code 1 attachment no. p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 529

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 13	T. 2 N. R 2 E.	K-5, L-5, L-6,
2. PROPERTY CONTROLLING IN SECTION	T.	S. R. E. W.
3. MISCELLANEOUS PROPERTY IN SECTION	T.	S. R. E. W.
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

FILED

FEB 3 8 39 AM '76

REGISTER OF DEEDS

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on 8-7 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ..... 19... found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-5 Unknown
L-5 Unknown
L-6 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-5 RR Spike
L-5 ½" Iron
L-6 Iron set

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-5 NW Corner
S 22°W 75.39 Nail W/S 32" Oak
S 10°E 52.23 Nail W/S Telephone pole
S 75°E 96.11 Nail W/S 18" Maple

L-6 Center Section
N 0.91 Nail W/W 20" Hickory
W 8.55 Nail W/S 10" Oak
S 9.83 Nail S/S ~~20~~ Oak 20"

L-5 N¼ Corner
S 33°E 32.77' SW side 14" Tree (Hickory)
N 3° E 68.50' E side 14" Oak
N 55°E 80.15' NW side 14" Oak

SIGNED BY Oscar Boss DATE 1-29-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ..... CHIEF OF PARTY DATE .....

APPROVED AND SIGNED BY ..... MICHIGAN REGISTERED LAND SURVEYOR DATE .....

SURVEYOR'S MICHIGAN REGISTRATION NO. .....

927

FORMS APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 29, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township T 2 N, R 2 E/W L-5 corner code 1 attachment no.

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ~~ORIGINAL~~ DUPLICATE on file at REGISTER OF DEEDS

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N. R. 2 E.	L-5, K-6
2. PROPERTY CONTROLLING IN SECTION	T. S. R.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. S. R.	

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

LIBER 4 PG 72
FILED
Jun 30 11 43 AM '77
REGISTER OF DEEDS
INGHAM COUNTY, MICH.
REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Karol R. Piotrowski, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 5, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law.

A. Description of ~~original monument and evidence~~ and or subsequent restoration:

K-6 ½" Re-rod 6" deep
L-5 ½" Re-rod

B. Description of corner evidence found ~~and/or method applied in restoring or re-establishing corner~~:

K-6 Found ½" re-rod 6" deep
L-5 Found ½" re-rod

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-6 N85°W 20.8' to 24" Oak
S45°E 42.43' to 20" Hickory
S60°W 30.7' to 24" Oak

L-5 N45°E 47.75' to 10" Oak
NORTH 24.60' to 2" Pipe in center of stone pillar
S70°E 76.76' to 15" Nut tree

SIGNED BY Karol R Piotrowski DATE 6-5-75

SURVEYOR'S MICHIGAN REGISTRATION NO. 9615

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY CHIEF OF SURVEY PARTY DATE

APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR DATE

(SEAL)

STATE OF MICHIGAN — KAROL R. PIOTROWSKI — LAND SURVEYOR — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO.

1074

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1976

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

WHITE OAK T2N R2E

WHITE OAK township T 2 N, R 2 E/W L-5 corner code 2 attachment no. p.1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

LIBER 3 PG 529

FOR CORNERS OF —	LOCATED IN —	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 13 T. 2 N. R 2 E.		K-5, L-5, L-6,
2. PROPERTY CONTROLLING IN SECTION ____ T ____ S. R. ____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION ____ T ____ S. R. ____ E. W.		

4. LOT NO. ____ RECORDED PLAT ____

5. PRIVATE CLAIMS ____

FILED

FEB 3 8 39 AM '76

REGISTER OF DEEDS

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Bosa, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on 8-7, 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-5 Unknown
L-5 Unknown
L-6 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-5 RR Spike
L-5 ½" Iron
L-6 Iron set

C. Description of monuments for corner and accessories established to perpetuate locating the position of the corner:

K-5 NW Corner
S 22°W 75.39 Nail W/S 32" Oak
S 10°E 52.23 Nail W/S Telephone pole
S 75°E 96.11 Nail W/S 18" Maple

L-6 Center Section
N 0.91 Nail W/W 20" Hickory
W 8.55 Nail W/S 10" Oak
S 9.83 Nail S/S ~~20"~~ Oak 20"

L-5 N¼ Corner
S 33°E 32.77' SW side 14" Tree (Hickory)
N 3° E 68.50' E side 14" Oak
N 55°E 80.15' NW side 14" Oak

SIGNED BY Oscar Bosa DATE 1-29-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ____ (Chief of Survey Party) DATE ____

APPROVED AND SIGNED BY ____ (Michigan Registered Land Surveyor) DATE ____

SURVEYOR'S MICHIGAN REGISTRATION NO. ____

Form No. 551 (2775) Lansing Blue Print & Co., Inc., Lansing, Mich.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 20, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

927

WHITE OAK township T 2 N, R 2 E/W L-6 corner code 1 attachment no. p. 1 of 1

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ~~DUPLICATE~~ ORIGINAL on file at REGISTER OF DEEDS

1777
WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 2 PC 111

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 24	T. 2 N. S. R. 2 E. W.	L-7, L-8, M-7, M-8
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

FILED
Oct 26 10 01 AM '72
REGISTER OF DEEDS
Paul M. Curtis
INGHAM COUNTY, MICH.
REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Ross, do hereby certify that under requirements of P.A.74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on Sept. 22, 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

L-7: Unknown
L-8: Unknown
M-7: Unknown
M-8: Unknown

B. Description of corner evidence found and/or method applied in retracing or re-establishing corner:

L-7: 1/2" pipe found
L-8: 1/2" pipe found
M-7: 1/2" iron found
M-8: 1/2" iron found

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-7: 1/2" pipe
N.2°E. 27.3 PK East side 20" tree
S.65°W. 39.3 Nail south side 26" Oak
S.21°E. 21.44 Lg. nail E. side 10" tree

L-8: 1/2" pipe
S.62°W. 17.5 Nail north side 8" Oak
North 19.45 Nail west side tree
East 36.25 Nail north side 42" Maple

M-7: 1/2" iron
N.67°W. 76.92 Nail south side 26" Hickory
S.14°W. 112.6 Nail east side 24" Hickory
S.50°E. 39.14 Nail West side 18" Oak
N.06°E. 24.03 Nail top of 36" stump

M-8: 1/2" iron
N.49°W. 24.35 Nail south side 14" twin Hick.
S.59°W. 36.0 Nail north side 30" maple
S.26°E. 39.55 Nail west side 10" Maple
West 33.14 1/2" iron

SIGNED BY Oscar Ross DATE 10-23-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (Chief of Survey Party) DATE _____

APPROVED AND SIGNED BY _____ (Michigan Registered Land Surveyor) DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

1777

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 20, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

WHITE OAK

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 3 PG 531

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 13	T. 2 N. R. 2 E.	K-6, K-7, L-7
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	

4. LOT NO. _____ RECORDED PLAT _____

5. PRIVATE CLAIMS _____

FILED

Feb 3 8 39 AM '76

REGISTER OF DEEDS

Carol M. Lewis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Rosa, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on K-7 1973, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

K-6 Unknown
K-7 Unknown
L-7 Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-6 ½" Iron
K-7 ½" Iron
L-7 ½" pipe

C. Description of monument (or corner and accessories established to perpetuate locating the position of the corner:

K-6 W¼ Corner
S 59°W 31.02' Spike in NW side 24" Oak
N 71°W 21.07' Spike in N side 22" Oak
S 43°E 42.61' Spike in SW side 18" Hickory

L-7 S¼ Corner
N 2°E 27.3 P.K.Nail E/S 20" Tree
S 65°W 39.1 Nail S/S 26" Oak
S 21°E 21.41 Lg. Nail E/S 10"Tree

K-7 SW Corner
N 53°W 38.95 Spike in E side Tele pole
N 40°E 47.39 Spike in SE side 36" Tree
S 43°W 81.35 centerline Street sign pole

SIGNED BY Oscar Rosa DATE 1-29-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
(Chief of Survey Party)

APPROVED AND SIGNED BY _____ DATE _____
(Michigan Registered Land Surveyor)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

928 Form No. 10-1570 (Supersedes prev. 9 FD-GAD-1570, which...)

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, MAY 20, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK T 2 N, R 2 E/W 1-7 2 Plat 1

INGHAM COUNTY-WHITE OAK TWP.

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N., R. 2 E.	M-5
2. PROPERTY CONTROLLING IN SECTION ___	T. ___ N./S., R. ___ E./W.	
3. MISCELLANEOUS PROPERTY IN SECTION ___	T. ___ N./S., R. ___ E./W.	

4. LOT NO. ______, RECORDED PLAT ______

5. PRIVATE CLAIMS ______

L.5P.256

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Ronnie M. Lester, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 16, 19 79, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ______, 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

M-5

Post set in original government survey by Joseph Wampler dated between Nov. 22 and 30, 1825.

Corner set as a stone in a survey by T.J. Brown, County Surveyor, Jan. 25-27, 1869 (v.3, p.45).

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

M-5

Excavated a hole 10' x 10' to an average depth of 1.5' at the intersection of the centerlines of Kane Road and Iosco Road west. Found a bolt 1½" x ¼", pieces of broken china, and a large rock 11½" x 6 3/4" lying beside each other on the centerline of Kane Road and ± 3.0' north of the centerline of Iosco Road west. Measured ± 2667' west to L-5 and ± 2656' south to M-6, both measurements in close accord to G.L.O. distances. Accepted large rock for corner as called for in survey by T.J. Brown, County Surveyor.

Excavation conducted by Ingham County Survey and Remonumentation Project crew.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-5

SE Corner, Section 12, T2N-R2E

Set 4" x 36" concrete monument with ½" x 38" rerod and cap #18998 in location of large rock described above:

Nail & tag, #18998, west side 20" Walnut, NE, 62.41'

Nail & tag, #18998, northeast side 36" Oak, SE, 92.56'

Nail & tag, #18998, northeast side 30" Maple, NW, 44.94'

Nail & tag, #18998, south side 32" Maple, WNW, 95.74'

SIGNED BY Ronnie M. Lester DATE 7/6/79

SURVEYOR'S MICHIGAN REGISTRATION NO. 18998

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

SIGNED BY ______ DATE ______

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY [signature] DATE 7-11-79

MICHIGAN REGISTERED LAND SURVEYOR

Director, Ingham County Survey and Remonumentation Project

(SEAL) STATE OF MICHIGAN · RONNIE M. LESTER · LAND SURVEYOR · NO. 18998 · REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 17624

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

INGHAM COUNTY-WHITE OAK TWP.

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N. ~~S.~~, R. 2 E. ~~W.~~	M-6
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

L. 5, P. 236

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Ronnie M. Lester, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 19, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

M-6
Post set in original government survey by J. Wampler dated between November 22 and 30, 1825.
Corner identified as post in a survey by T.J. Brown, County Surveyor, dated January 25-27, 1869 (v.3, p.45).

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
M-6
Excavated a hole 4' x 4' on the centerline of Kane Road and on fence/tree line to west. Found small stones set in a large "X" pattern, the center being on the centerline of Kane Road and on extended fence/tree line west. Also found a large stone (1' x 2") directly beneath formation, with flat side up. Set ½" iron in location of center of "X" formation and large stone on November 18, 1977 until further measurements could verify location. Measured south + 2655' to M-7 in close accord with G.L.O. distance. Accepted center of stone formation for corner. Excavation conducted by Ingham County Survey and Remonumentation Project crew.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-6
E¼ Corner, Section 13, T2N-R2E
Set 4" x 36" concrete monument with ½" x 38" rerod and cap #18998 in location of stone formation described above:
Nail & tag, #18998, southeast side 36" Oak, SW, 28.77'
Nail & tag, #18998, north side 14" Hickory, WNW, 24.90'
Nail & tag, #18998, south side 10" Hickory, ENE, 26.20'
Nail & tag, #18998, southwest side 11" Oak, SE, 38.39'

SIGNED BY Ronnie M. Lester DATE April 3, 1979

SURVEYOR'S MICHIGAN REGISTRATION NO. 18998

(SEAL)

STATE OF MICHIGAN — RONNIE M. LESTER — LAND SURVEYOR — No. 18998 — REGISTERED LAND SURVEYOR

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY Gary D. Lester DATE 4-20-79
MICHIGAN REGISTERED LAND SURVEYOR
Director, Ingham County Survey and Remonumentation Project

(SEAL)

STATE OF MICHIGAN — GARY D. LESTER — LAND SURVEYOR — No. 17624 — REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 17624

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED

SOURCE: CORNER RECORDATION CERTIFICATE

TRANSCRIBED from ORIGINAL ~~DUPLICATE~~ on file at REGISTER OF DEEDS

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

LIBER 2 PG 111

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY 24	T. 2 N. R. 2 E.	L-7, L-8, M-7, M-8
2. PROPERTY CONTROLLING IN SECTION	T. N. S. R. E.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E.	
4. LOT NO.	RECORDED PLAT	
5. PRIVATE CLAIMS		

FILED

Oct 26 10 03 AM '72

REGISTER OF DEEDS

Enid M. Louis

INGHAM COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Oscar Boss do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on Sept. 22, 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

L-7: Unknown
L-8: Unknown
M-7: Unknown
M-8: Unknown

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

L-7: 1/2" pipe found
L-8: 1/2" pipe found
M-7: 1/2" iron found
M-8: 1/2" iron found

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-7: 1/2" pipe
N.2°E. 27.3 PK East side 20" tree
S.65°W. 39.3 Nail south side 26' Oak
S.21°E. 21.44 Lg. nail E. side 10" tree

L-8: 1/2" pipe
S.62°W. 17.5 Nail north side 8" Oak
North 19.45 Nail west side tree
East 16.25 Nail north side 42" Maple

M-7: 1/2" iron
N.67°W. 76.92 Nail south side 26" Hickory 77.16
S.14°W. 112.6 Nail east side 24" Hickory 12.35
S.50°E. 39.14 Nail West side 18" Oak
N.66°E. 24.03 Nail top of 36" stump 38.85

M-8: 1/2" iron
N.49°W. 24.35 Nail south side 14" twin Hick.
S.59°W. 36.0 Nail north side 30" maple
S.26°E. 39.55 Nail west side 10" Maple
West 33.14 1/2" iron

SIGNED BY Oscar Boss DATE 10-23-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 13574 (MR)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ CHIEF OF SURVEY PARTY DATE _____

APPROVED AND SIGNED BY _____ MICHIGAN REGISTERED LAND SURVEYOR DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

377 Form No. [illegible]

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 20, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS

WHITE OAK township | T 2 N, R 2 E | M-7 corner code | 1 attachment no. | p.1 of 1