

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 8 PAGE 209

For corners in

INGHAM

(County)

Located In:

Corner Code ~~##~~

White Oak Township

1. Public Land Survey

T 2N R 2E

A-5

2. Property Controlling
in Section

S T R

3. Miscellaneous
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

FILED

SEP 14 8 43 AM '94

REGISTER OF DEEDS

Paula Johnson

INGHAM COUNTY, MICH.

Register of Deeds Stamp & File Number

I, R. W. Steadman, in a field survey on June 3, 1994,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor, 150 links north of M-5, T2N, R1E; bearing trees: 15" Ash S14-1/2°E 50 links and 5" Tamarack N86-3/4°E 40-1/2 links.
- 2). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson used this corner, noting the original bearing trees for witnesses, but does not describe the monument.

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron pipe and cap 11370 in good condition in monument box in center of Meech Road and about 5 feet North of center of Iosco Road. 1976 witnesses gone, except for M-5, T2N, R1E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Left 1/2" iron pipe and cap 11370 in place as found in monument box to mark the corner, and took the following witnesses (bearings are magnetic):

Set nail and tag 11370 in W. side 20" Walnut S33°W 141.39 feet
Set nail and tag 11370 in SW side 12" Elm S16°E 131.82 feet
Set nail and tag 11370 in SW side 20" Walnut S61°E 149.74 feet

(Continued on back)

Signed by Richard W. Steadman Date July 12, 1994

Surveyor's Michigan License No. 11370

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

P.A. 345 INGHAM COUNTY

PEER APPROVED 7/13/94 RZ

REVISED MAY 14, 1975
REVISED JAN., 1983

A-5, T2N, R2E

Part A - Continued

- 3). 4-26-1976: Land Corner Recordation Certificate (Rec. 1-16-79, L5-P143), R. W. Steadman L.P.S. 11370 "dug hole in the intersection of Meech and Iosco Roads, but found nothing. Re-established the corner on the township line as defined by the quarter corner next north for T2N, R1E and the corresponding section corner for T2N, R1E (see Items 4). and 5). below), and at the USPLS recorded jog distance south of it. Set 1/2" iron pipe and monument box to mark the corner. Witnesses: telephone pole S20°E 80.71 ft., wood anchor post S64°E 87.64 ft., 20" Maple N71°E 76.17 ft. Corner for T2N, R1E (set 3/4" iron pipe and monument box - 1973) South 99 ft." Note: A-5 is North of M-5, not South of it.
- 4). 6-22-1973: Land Corner Recordation Certificate for M-4, T2N, R1E (Rec. 1-16-79, L5-P147), R. W. Steadman "dug hole in Meech Road opposite fence West, and about 2 ft. below the surface, found a long pointed stone with a hub cap alongside, and broken crockery and small stones around. Raised location of stone to surface with 3/4" iron pipe and set monument box. Witnesses: 24" Maple WNW 23.08 ft., 22" Maple SSE 131.51 ft., wood culvert post NNE 83.03 ft."
- 5). 6-25-1973: Land Corner Recordation Certificate for M-5, T2N, R1E (Rec. 1-16-79, L5-P146), R. W. Steadman "dug hole in the intersection of Meech and Iosco Roads but found nothing. Re-established corner by proportional measurements from possession evidence North, South, and West. Set 3/4" iron pipe in monument box to mark the corner. Witnesses: 30" Maple NNW 66.94 ft., 14" Walnut SSW 74.63 ft., Telephone pole SW 59.72 ft., Telephone pole NE 39.15 ft."

Part C - Continued

Set nail and tag 11370 in S. side 12" Elm N72°E 70.80 feet
Set nail and tag 11370 in S. side 15" Elm N68°W 66.66 feet
Found 1/2" iron rod and cap marked "Ingham Temp. Pt." S07°E 3.94 feet
Found 1/2" iron pipe and cap 11370 in monunent box (corner for T2N, R1E)
S04°W 99.00 feet

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 8 PAGE 211
FILED

For corners in

Ingham

(County)

Located In:

Corner Code =#

White Oak Township

1. Public Land Survey

T 2N R 2E

A-6

T R

T R

T R

S T R

S T R

S T R

S T R

2. Property Controlling
in Section

3. Miscellaneous

Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

SEP 14 8 43 AM '94

REGISTER OF DEEDS

Paula Johnson

INGHAM COUNTY, MICH.

Register of Deeds Stamp & File Number

I, R. W. Steadman, in a field survey on June 3, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

- 1). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson appears to
have established this closing quarter corner, giving the following bearing
trees but no monument description: 12" B. Ash S85°W 68 links and 16" B. Ash
S44-1/2°W 35-1/2 links. Establishment of closing quarter corners was not
included in the procedure for the United States Survey of the Public Lands.
- 2). 4-26-76: Land Corner Recordation Certificate (Rec. 1-16-79, L5-P142), R. W.
Steadman L.P.S. 11370 "dug hole in Meech Road but found nothing."

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 5/8" iron rod and cap in monument box in center of Meech Road; rod was in
good condition but cap was illegible. Removed existing rod and replaced it
with standard Ingham County Remonumentation 3/4" iron rod and cap.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P.A. 345, PS 11370" in monument box
and took the following witnesses (bearings are magnetic):

Found 3" steel fence post S86°E 27.03 feet
Set nail and tag 11370 in W. side 15" Elm N24°E 82.68 feet
Set nail and tag 11370 in W. side 12" Elm S15°E 87.08 feet
Set nail and tag 11370 in E. side 8" Willow N06°W 171.51 feet

(Continued on back)

Signed by Richard W. Steadman

Date July 12, 1994

Surveyor's Michigan License No. 11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 7/13/94 M

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

2652

A-6, T2N, R2E

Part A - Continued

2). Continued

"Re-established corner opposite fence East and on township line as defined by corresponding quarter corner for T2N, R1E and the next section corner North for T2N, R1E (see Items 3 and 4 below). Set 5/8" iron rod and monument box to mark the corner. Witnesses: Wood anchor post S21°W 69.12 ft. (gone-1994), C/L steel anchor post S86°E 27.03 ft., 4" Elm N22°E 82.54 ft."

- 3). 6-25-1973: Land Corner Recordation Certificate for M-5, T2N, R1E (Rec. 1-16-79, L5-P146), R. W. Steadman "dug hole in the intersection of Meech and Iosco Roads but found nothing. Re-established corner by proportional measurements from possession evidence North, South, and West. Set 3/4" iron pipe in monument box to mark the corner. Witnesses: 30" Maple NNW 66.94 ft., 14" Walnut SSW 74.63 ft., Telephone pole SW 59.72 ft., Telephone pole NE 39.15 ft."
- 4). 6-14-1979: Land Corner Recordation Certificate for M-6, T2N, R1E (Rec. 9-19-79, L5-P302), R. M. Lester L.P.S. 18998 found a 1/2" iron above a wood stake with stones around it; set concrete monument witnessed by: 8" Aspen NE 52.17 ft., 8" Elm SE 31.87 ft., 5" Sassafras SSW 68.62 ft., 3" iron gate post WSW 36.55 ft., 1/2" iron in monument box (A-6, T2N, R1E) North 65.65 ft. Note: the 1/2" iron above the wood stake was found and used to define the township line in 1973.
- 5). 6-02-76: Certified Survey Map (Rec. 6-10-76, L2-P725), R. W. Steadman calls for monument and witnesses given in 2). above.
- 6). 9-21-1977: Land Corner Recordation Certificate (Rec. 7-13-78, L4-P247), G. M. Young L.P.S. 17640 "found iron in cast iron monument box" witnessed by 3" steel fence post East 27.10 ft., 3" steel gate post SW 90.00 ft. (gone-1994), 3" steel fence post WSW 84.55 ft. (gone-1994).
- 7). 9-21-1977: Certified Survey Map (Rec. 12-21-77, L3-P160), G. M. Young calls for monument and witnesses given in 6). above.
- 8). 10-20-1977: Land Corner Recordation Certificate (Rec. 8-11-78, L4-P284), A. C. Williams P.L.S. 21275 found 1/2" iron rod in monument box witnessed by 3" steel fence post East 27.10 ft., 3" steel gate post SW 90.00 ft., 3" steel fence post WSW 84.55 ft.
- 9). 10-20-1977: Certified Survey Map (Rec. 11-22-77, L3-P103), A. C. Williams calls for witnesses given in 8). above with no mention of the type of monument.

Part C - Continued

Set nail and tag 11370 in NW side 18" Oak S56°W 110.20 feet
C/L 3" steel gate post S28°W 83.69 feet
Found concrete monument (corner for T2N, R1E) S02°W 65.65 feet

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

INGHAM

(County)

White Oak Township

Located In:

Corner Code #

1. Public Land Survey

T 2N R 2E

A-7

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

SEP 14 8 44 AM '94

REGISTER OF DEEDS

Daniel Johnson

INGHAM COUNTY, MICH.

Register of Deeds Stamp & File Number

I, R. W. Steadman, in a field survey on June 3, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor, 80 lks. North of corner for T2N, R1E; bearing trees: 48" Oak S51°E 46 lks. and 12" Beech N66°E 24 lks.
- 2). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson used this corner, noting the original bearing trees as witnesses, but does not describe the monument. Marginal note: "K (A-7) of the above plat was

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron rod in monument box in State Hwy. M-36/Dansville Road. Removed existing rod and replaced it with standard Ingham County Remonumentation 3/4" iron rod and cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P.A. 345, PS 11370" in monument box and took the following witnesses (bearings are magnetic):

Found nail and tag 17640 in N. side Telephone Pole N80°E 31.15 feet
 Found nail and tag 17640 in N. side Power Pole S56°E 130.82 feet
 Found nail and tag 17640 in N. side Power Pole S16°W 130.93 feet

(Continued on back)

Signed by

Richard W. SteadmanDate July 12, 1994

Surveyor's Michigan License No.

11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 7/13/94 RL

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN., 1983

A-7, T2N, R2E

Part A - Continued

2). Continued

re-established by order of the Commissioners November 16, 1874 by W. H. Rayner, Deputy County Surveyor. 10" Elm N19-1/2°W 113 lks., 5" Elm N89°W 87-1/2 lks." Additional marginal note: "For the location of this corner (A-7), see note on Page 139." In a marginal note dated 8-03-1882 on Page 139 of Volume 1, County Surveyor A. P. Drake and Deputy T. J. Brown re-established M-7 for T2N, R1E equidistant from M-6 and M-8, and then set A-7 for T2N, R2E 80 links north of it, witnessed by a 12" Elm S77-1/2°W 85-1/2 links (56.43 ft.) and a 24" Elm N21-3/4°W 91-1/2 links (60.39 ft.).

- 3). 1-12-1855: Volume 2, Page 242, County Surveyor Anson Jackson used this corner, noting the original bearing trees as witnesses, but does not describe the monument. Also, Rayner's 1874 witnesses given in 2). above have been written in. There is also a marginal note by Drake and Brown repeating their re-establishment of M-7 and A-7 described in 2). above, but dated 8-03-1880.
- 4). January, 1969: County Road Commission Corner Grid Sheet calls for this corner to be marked by brick and tile, to be 52.45 feet North of M-7, T2N, R1E, and witnessed by 24" Elm WSW 57.0 feet and 30" Elm NNW 61.5 feet. (Drake and Brown witnesses?)
- 5). 6-14-1977: Land Corner Recordation Certificate (Rec. 9-23-77, L4-P91), G. M. Young L.P.S. 17640 found 1/2" rod flush with asphalt witnessed by: nail and tag in Telephone pole N80°E 31.15 ft., nail and tag in Power pole S45°E 130.90 ft., nail and tag in Power pole S10°W 130.93 ft.
- 6). 6-21-1977: Certified Survey Map (Rec. 9-23-77, L3-P15), G. M. Young calls for monument and witnesses given in 5). above.
- 7). 9-21-1977: Certified Survey Map (Rec. 12-21-77, L3-P160), G. M. Young calls for 1/2" iron witnessed by: nail and tag in T.P. NE 31.20 ft., nail and tag in P.P. SE 130.95 ft., nail and tag in T.P. SW 131.05 ft.
- 8). 10-20-1977: Certified Survey Map (Rec. 11-22-77, L3-P103), A. C. Williams L.P.S. 21275 calls for the witnesses given in 7). above, but gives no monument description.
- 9). April, 1985: Certified Survey Map (Rec. 5-06-85, L4-P1023), R. M. Lester L.P.S. 18998 calls for a 1/2" bar in monument box witnessed by: M-7, T2N, R1E South 52.81 ft., nail and tag in Telephone pole N80°E 31.15 ft., nail and tag in Power pole S45°E 130.90 ft., nail and tag in Power pole S10°W 130.93 ft.

Part C - Continued

N. edge of Hwy. M-36 sign post S84°W 114.61 feet
SW corner of foundation for house #2517 N71°E 149.64 feet
M-7, T2N, R1E (paved over, got signal from magnetic locator) S02°W 52.8 feet

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

OCT 3 1 16 PM '94

REGISTER OF DEEDS
Paula Johnson
INGHAM COUNTY, MICH.

For corners in

INGHAM

(County)

Located In:

Corner Code ##

White Oak Township

1. Public Land Survey

T 2N R 2E

B-5

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, R. W. Steadman, in a field survey on June 14, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor; bearing trees: 6" Sugar N21°W 19 links and 12" Sugar S72°W 8 links.

2). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson used this corner and notes the original bearing trees as witnesses, but does not describe the monument.

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron pipe and cap in monument box in center of Iosco Road; pipe was in good condition but cap was unreadable. Replaced the pipe with standard Ingham County Remonumentation 3/4" iron rod and cap.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P. A. 345, PS 11370" in monument box and took the following witnesses (bearings are magnetic):

Found nail and tag 11370 in N. side 20" stump S61°E 61.92 feet
Set nail and tag 11370 in W. side 22" Maple N04°W 27.37 feet
Set nail and tag 11370 in N. side 12" Hickory S47°W 33.63 feet
Set nail and tag 11370 in S. side triple 8" Elm N56°W 59.58 feet
Set nail and tag 11370 in S. side twin 10" Elm N81°E 88.93 feet
Set nail and tag 11370 in N. side 14" Hickory S64°E 75.60 feet

Signed by Richard W. Steadman

Date September 9, 1994

Surveyor's Michigan License No. 11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 9/14/94

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

B-5, T2N, R2E

Part A - Continued

- 3). 4-26-76: Land Corner Recordation Certificate (Rec. 1-06-79, L5-P145), R. W. Steadman L.P.S. 11370 "dug hole in Iosco Road but found nothing; location falls in road cut area. Re-established corner in center of road opposite fence lines North and South. Set 1/2" iron pipe and monument box to mark the corner. Witnesses: 8" Hickory S47°W 34.09 feet, 20" Oak S62°E 61.90 feet, 18 Maple N08°W 27.55 feet".
- 4). 6-02-76: Certified Survey Map (Rec. 6-10-76, L2-P725), R. W. Steadman calls for the monument and witnesses given in 3). above.
- 5). 10-18-1988: Private Records of D. L. Clifford L.P.S. 25837 surveying for the subsequently cancelled Supercollider Project - surveyed Section 18, T2N, R2E, and established coordinates for the corners. Computation of distances from his coordinates indicates that it is 2668.61 feet East, 2671.00 feet South, and 2148.24 feet West to the adjacent corners.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Oct 3 1 17 PM '94

REGISTER OF DEEDS

INGHAM COUNTY, MICH.

For corners in

INGHAM

(County)

White Oak Township

Located In:

Corner Code =#

1. Public Land Survey

T 2N R 2E

B-6

2. Property Controlling
in Section

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, R. W. Steadman, in a field survey on July 12, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson appears to have established this section center, giving the following witnesses but no monument description: 12" Maple N38-1/2°E 12 links (7.92 feet) and 24" W. Oak S68-1/2°E 32 links (21.12 feet). Establishment of section centers was not included in the procedure of the U. S. Survey of the Public lands.

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1-1/4" iron pipe in rock pile 3.2 feet North and 3.1 feet East of fence post at intersection of fences running North, South, East, and West. Replaced 1-1/4" pipe with standard Ingham County Remonumentation 3/4" iron rod and cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P. A. 345, PS 11370" to mark the corner and took the following witnesses (bearings are magnetic):

Found nail and tag 25837 in N. side 18" Hickory N86°W 62.52 feet
 Found nail and tag 25837 in N. side 6" Maple S65°E 11.18 feet
 Found nail and tag 25837 in SW side twin 12" Box Elder N15°W 21.52 feet
 Found 22" Hickory Stump N42°E 7.9 feet
 Set nail and tag 11370 in W. side 14" Wild Cherry S01°E 30.79 feet
 Set nail and tag 11370 in S. side 8" Wild Cherry East 21.63 feet

Signed by

Richard W. SteadmanDate September 12, 1994

Surveyor's Michigan License No.

11370

P.A. 345 INGHAM COUNTY

PEER APPROVED

9/14/94 M

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

B-6, T2N, R2E

Part A - Continued

- 2). 10-18-1988: Private records of D. L. Clifford L.P.S. 25837, surveying for the subsequently cancelled Supercollider Project, notes: "found remnants of wood stake under pile of stones @ 7.9 feet from 22" Hickory stump (new cut). Rings indicate stump is 180 years old +/- . Took stump to be Maple witness from A. Jackson's 1839 survey. Set 1-1/4" iron pipe on wood. N & C 25837 in 6" Hick. E. 11.2 feet, N & C 25837 in 18" Hick. W. 65.2 feet, N & C 25837 in 12" Quad. Oak N05°W 21.52 feet, 22" Hick. Stump N38°E 7.9 feet". Clifford states that found corner is 3.7 feet North and 3.9 feet East of intersection of quarter lines. Computation of distances from his coordinates indicates that it is 2671.00 feet North, 2657.08 feet East, 2652.23 feet South, and 2161.65 feet West to the adjacent corners.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

OCT 3 1 17 PM '94

REGISTER OF DEEDS

Paula Johnson
INGHAM COUNTY, MICH.

For corners in

INGHAM

(County)

Located In:

Corner Code #

White Oak Township

1. Public Land Survey

T 2N R 2E

C-5

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, R. W. Steadman, in a field survey on June 14, 1994,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor; bearing
trees: 14" Sugar S19°W 18 links and 3" Ironwood N55°E 12 links.

2). I find no further mention of this corner in available records until the
Land Corner Recordation Certificate listed in 3). below.

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found concrete monument with cap 18998 in good condition in monument box in
center of Iosco Road.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Left concrete monument with cap 18998 in monument box as found to mark the
corner and took the following witnesses (bearings are magnetic):

Found nail and tag 18998 in W. side Power Pole N10°E 25.42 feet

Found nail and tag 18998 in E. side 15" Hickory S16°W 87.33 feet

NW corner foundation House #3010 S19°E 189.71 feet

Set nail and tag 11370 in SW side 22" Chinese Elm S33°E 41.15 feet

Set nail and tag 11370 in S. side 28" Elm N76°E 83.54 feet

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													



Signed by Richard W. Steadman Date September 9, 1994

Surveyor's Michigan License No. 11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 9/14/94 M

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

C-5, T2N, R2E

Part A - Continued

- 3). 4-03-81: Land Corner Recordation Certificate (Rec. 6-04-81, L6-P193), R. M. Lester L.P.S 18998 indicates excavation was made but nothing found. Corner was re-established on road centerline opposite fence North. "Measured South 2687.66 feet, North 2643.24 feet, West 2668.97 feet, and East 2625.19 feet. Excavation by Ingham County Survey and Remonumentation Project Crew". A 4" by 36" concrete monument with collar and cap 18998 was set and witnessed by: nail and tag 18998 in W. side Power Pole N10°E 25.44 feet, nail and tag 18998 in S. side 10" Hawthorne N70°E 83.65 feet, nail and tag 18998 in SW side 12" Cottonwood S70°E 41.47 feet, nail and tag in E. side 12" Hickory S10°W 87.38 feet.
- 4). 10-18-94: Private records of D. L. Clifford L.P.S. 25837 surveying for the subsequently cancelled Supercollider Project - surveyed Section 18, T2N, R2E, and established coordinates for the corners. Computation of distances from his coordinates indicates that it is 2687.52 feet South and 2668.61 feet West to the adjacent corners.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

OCT 3 1 17 PM '94

REGISTER OF DEEDS
Paul Johnson
INGHAM COUNTY, MICH.

For corners in

INGHAM

(County)

Located In:

Corner Code ##

White Oak Township

1. Public Land Survey

T 2N R 2E

C-6

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, R. W. Steadman, in a field survey on July 11, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor; bearing trees: 20" W. Oak S57-3/4°W 22 links and 20" W. Oak S73-3/4°E 10 links. In the margin of the County copy of the USPLS Field Notes is noted "New: 12" Elm S16°W 25-1/2 and 16" R. Oak S45°E 222-1/2 or 22-1/2".

2). 1-14-1869: Volume 3, Page 43, Deputy County Surveyor T. J. Brown used this
(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron rod and cap 18998; replaced it with a standard Ingham County Remonumentation 3/4" iron rod and cap.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P. A. 345, PS 11370" to mark the corner and took the following witnesses (bearings are magnetic):

Found nail and tag 18998 in S. side 14" Walnut S24°E 40.95 feet
Found nail and tag 18998 in S. side Fence Post N84°W 11.95 feet
Set nail and tag 11370 in E. side multiple 12" Poplar S28°W 23.58 feet
Set nail and tag 11370 in N. side 12" Walnut S83°E 24.47 feet
Set nail and tag 11370 in S. side 4" Ash N69°W 10.69 feet

Signed by Richard W. SteadmanDate September 9, 1994Surveyor's Michigan License No. 11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 9/14/94 MCFORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

C-6, T2N, R2E

Part A - Continued

- 2). Continued:
corner and calls for a post from which a 20" W. Oak bears S57-3/4°W 22 links.
- 3). 3-03-81: Land Corner Recordation Certificate (Rec. 6-04-81, L6-P192), R. M. Lester L.P.S. 18998 states "Investigation revealed no evidence of physical monumentation. Set corner at intersection of E-W fence on line between C-7 and C-5. Measured North 2687.65 feet and South 2648.72 feet. County Surveyors Notes 1/2 mile East reflect excess in North 1/2 of Section also. Corner falls on West side of old roadway which is now a two track trail. Investigation conducted by Ingham County Survey and Remonumentation Project Crew". A 1/2" iron rod and cap 18998 was set and witnessed by: nail and tag 18998 in SW side 12" Ash S10°E 33.13 feet (gone-1994), nail and tag 18998 in S. side 10" Ash S60°E 40.95 feet, nail and tag in S. side fence post West 11.95 feet, nail and tag 18998 in E. side twin Ash S20°W 24.02 feet.
- 4). 10-18-88: Private records of D. L. Clifford L.P.S. 25837 surveying for the subsequently cancelled Supercollider Project - surveyed Section 18, T2N, R2E, and established coordinates for the corners. Computation of distances from his coordinates indicates that it is 2687.52 feet North, 2648.67 feet South, and 2657.08 feet West to the adjacent corners.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

OCT 26 9 14 AM '94

For corners in

INGHAM

(County)

White Oak Township

Located In:

Corner Code =#

REGISTER OF DEEDS

Paula Johnson
INGHAM COUNTY, MICH.

1. Public Land Survey

T 2N R 2E

B-7

2. Property Controlling
in Section

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, R. W. Steadman, in a field survey on June 7, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor; bearing trees: 4" Beech S24°E 3-1/2 links and 8" Beech S58-1/2°W 5 links.

2). 12-28-1839: Volume 1, Page 152, County Surveyor Anson Jackson used this corner and noted the original bearing trees as witnesses, but does not describe the monument.

(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron rod and cap in monument box in State Hwy. M-36/Dansville Road opposite fence to North; cap unreadable. I believe that the Road Commission records are the best available information as to the location of this corner; that the 1-1/4" pipe found by Young is the 1" iron called for by the Road Commission; and based on the remaining witnesses, that the 1/2" rod found is the one set by Young above the 1-1/4" pipe. Replaced 1/2" rod with standard Ingham County Remonumentation 3/4" iron rod and cap.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P. A. 345, PS 11370" in monument box and took the following witnesses (bearings are magnetic):

Set nail and tag 11370 in W. side 22" Wild Cherry N05°E 54.18 feet
Set nail and tag 11370 in S. side twin 18" Elm N82°E 147.95 feet
Set nail and tag 11370 in N. side Power Pole S55°E 145.09 feet
Set nail and tag 11370 in N. side 10" Clump Apple N77°W 97.14 feet
Set nail and tag 11370 in N. side 20" Box Elder S80°W 129.26 feet

(Continued on back)

Signed by Richard W. Steadman Date September 9, 1994Surveyor's Michigan License No. 11370

2676

P.A. 345 INGHAM COUNTY
PEER APPROVED 10/12/94 M

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

B-7, T2N, R2E

Part A - Continued

- 3). 12-10-1874: Volume 3, Page 92, County Surveyor T. J. Brown used this corner, and notes a post from which a 4" Tame Cherry bears S07°E 40-1/3 links (26.62 feet) and a 6" Tame Cherry bears S60°E 80-1/2 links (53.13 feet).
- 4). January 1969: County Road Commission Corner Grid Sheet calls for this corner to be marked by a 1" iron witnessed by a 10" Cherry SW 58.8 feet, a 4" Cherry NE 30.7 feet, and NW cor. house wall SE 95.3 feet (all witnesses gone - 1994).
- 5). 12-16-75: Land Corner Recordation Certificate (Rec. 3-02-76, L3-P540), G. M. Young L.P.S. 17640 found a 1-1/4" iron pipe 3 feet under asphalt, raised to surface with a 1/2" iron rod and set monument box, and witnessed by: nail in 18" Cherry N05°W 54.51 feet, hash mark on top of concrete culvert N30°W 32.78 feet, nail in 24" Apple S45°W 97.29 feet.
- 6). 12-18-75: Certified Survey Map (Rec. 3-02-76, L2-P642), G. M. Young calls for monument and witnesses given in 5). above, and shows the 1/8 line fence next east (running south) midway between this corner and the section corner next east.
- 7). 6-21-77: Certified Survey Map (Rec. 9-23-77, L3-P15), G. M. Young calls for the monument and witnesses given in 5). above.
- 8). 9-21-77: Certified Survey Map (Rec. 12-21-77, L3-P160), G. M. Young notes that he found an iron in mon. box witnessed by: found nail w/tag in 24" Wild Cherry NNE 54.60 feet, set nail w/tag in P.P. SE 145.25 feet, found nail w/tag in 12" Apple Clump SW 97.30 feet.
- 9). 10-20-77: Certified Survey Map (Rec. 11-22-77, L3-P103), A. C. Williams L.P.S. 21275 notes the witnesses given in 8). above but does not describe the monument.
- 10). 10-18-1988: Private records of D. L: Clifford L.P.S. 25837 surveying for the subsequently cancelled Supercollider Project - surveyed Section 18, T2N, R2E, and established coordinates for the corners. Computation of distances from his coordinates indicates that it is 2167.25 feet (GL0: 32.54 chains = 2147.64 feet) West to A-7, 2652.23 feet North to B-6, and 2652.11 feet East to C-7.

Part C - Continued

C/L Top Phone Pedestal N49°W 52.25 feet

Found hash mark on Concrete Culvert N35°W 32.78 feet

Found nail and tag (reverse side out) in N. side Power Pole S55°E 145.21 feet

OCT 3 1 18 PM '94

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

INGHAM

(County)

Located In:

Corner Code #

White Oak Township

1. Public Land Survey

T 2N R 2E

C-7

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

REGISTER OF DEEDS

INGHAM COUNTY, MICH.

Register of Deeds Stamp & File Number

I, R. W. Steadman, in a field survey on June 7, 1994

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1). 1825: Wood post set by Joseph Wampler, U. S. Deputy Surveyor; bearing trees: 9" Elm S42°W 14 links and 10" Ash N49-1/2°W 24 links. In the margin of the County copy of the USPLS Field Notes is noted "New: 10" Ash S29°W 39-1/2."

2). 1-14-1869: Volume 3, Page 43, Deputy County Surveyor T. J. Brown used this
(Continued on back)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found uncapped 1/2" iron rod in monument box in State Hwy. M-36/Dansville Road. Only stumps of Young's cottonwood witnesses remain; fence post witness is gone. Replaced 1/2" rod with standard Ingham County Remonumentation 3/4" iron rod and cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" smooth iron rod and cap stamped "P. A. 345, PS 11370" in monument box and took the following witnesses (bearings are magnetic):

Cut cross on top of Concrete Culvert N63°E 57.48 feet
Set nail and tag 11370 in N. side twin 20" Cottonwood S52°E 84.68 feet
Set nail and tag 11370 in W. side 18" Cottonwood S07°E 45.05 feet
Set nail and tag 11370 in S. side 10" Elm N69°W 120.66 feet
Set nail and tag 11370 in E. side Anchor Post N10°W 32.32 feet

Signed by Richard W. Steadman Date September 10, 1994

Surveyor's Michigan License No. 11370

P.A. 345 INGHAM COUNTY

PEER APPROVED 9/14/94

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

2670



C-7, T2N, R2E

Part A - Continued

- 2). Continued:
corner and calls for a post from which a 10" B. Ash bears S29°W 39-1/2 links.
- 3). 12-16-75: Land Corner Recordation Certificate (Rec. 3-02-76, L3-P540), G. W. Young L.P.S. 17640 found a hex head iron rod 2.2 feet under the asphalt and raised it to the surface with a 1/2" iron rod and set a monument box witnessed by: nail in fence post N45°E 43.35 feet, nail in 24" cottonwood S30°E 52.16 feet, nail in 18" Cottonwood S30°W 49.07 feet.
- 4). 12-18-75: Certified Survey Map (Rec. 3-02-76, L2-P642), G. M. Young calls for the monument and witnesses given in 3). above, and shows the 1/8 line fence next west (running south) midway between this corner and the quarter corner next west.
- 5). 10-18-1988: Private records of D. L. Clifford L.P.S. 25837 surveying for the subsequently cancelled Supercollider Project - surveyed Section 18 and the east line of Section 19, T2N, R2E, and established coordinates for the corners. Computation of distances from his coordinates indicates that it is 2648.67 feet North, 2652.11 feet West, and 2658.61 feet South to the adjacent corners.